


Piping system for potable water supply

aquatherm **green**

Part of the Solution www.aquatherm.de



- 4 History_
- 5 About aquatherm
- 6 Application fields for plastic piping systems ___
- 8 Product overview

Product types___

- 12 General product information
- 15 Diameter
- 15 Pressure stages

Pipe structure variants

6 • Overview

17

- aquatherm green S
- o aquatherm green RP
- 17 aquatherm green UV
- o aquatherm green MF
- 21 Permissible working pressure

Characteristics and special features___

- 24 Material fusiolen®
- 26 Sustainability
- 28 Environmental Product DeclarationLEED-Certification
- 32 Fire protection

37 Processing possibilities

- Socket welding with manual welding device
- Socket welding with welding machine
- Socket welding/Butt welding
- Electric socket welding
- Saddle welding OT
- Electric welding jig
- 38 Chemical and thermal disinfection
- 39 Integration of non-plastic components in pressure applications
- 40 Hot water circulation systems in potable water applications
- 42 Certificates
- Comparison of the Water content per metre
- 46 Field of applications_
- 48 Potable water applicationsMaritime applications

Quality assurance_

- 2 "100 % Made in Germany"
- 53 Compliance with the system standard
- 53 Certificate

Planning services___

- Planning services
- ⁷ Efficiency optimisation
- 57 Coefficient of loss

References_

- 60 Gippsland Recreation and Aquatic Centre (GRAC)
- 62 Riu Plaza de España
- 4 Research vessels "Snow Dragon 1 and 2"
- 68 Chemical resistance
- 72 Warranty_
- 76 Transport and storage__
- 30 Article list__



2005

2010

2012

2013

2015

2018

2018

2019

2021

2022

2023

2024

market launch of the aquatherm red pipe and aquatherm black system

Christof, Dirk and Maik Rosenberg assume company management

system expansion of the pipe size to max. ø 630 mm

market launch of the material fusiolen® PP-RP

first certification of the energy management system

foundation of the sales company in North America

expansion of the industrial prefabrication operation

participation in the distribution company aquatherm iberica s.l.

Jan Kriedel takes over the management with Maik Rosenberg

opening of the new pipe extrusion plant

opening of the aquatherm Campus

opening of the new injection moulding facility

foundation of the sales company in England

aquatherm celebrates it's 50th anniversary

in accordance with ISO 14001

in accordance with ISO 50001

first certification of the environment management system

Revolution since 1973

It all began with a vision.

On 17 August 1973, Gerhard Rosenberg founded aquatherm GmbH - based in the garage and basement of his private home. The ambitious goal? To revolutionise the market as a pipe manufacturer. This vision gave rise to aquatherm, the world's leading manufacturer of plastic piping systems made of polypropylene for plant construction and building services.

The numerous product lines provide superior solutions in potable water applications, heating systems, fire sprinkler systems, air conditioning and refrigeration technology, as well as in surface heating and cooling systems.

Due to their special material properties, the aquatherm pipe systems convince by their diverse applica-

tion possibilities.

The aquatherm pipe systems can be used in all areas of new installation, repair and renovation.

aquatherm employs around 550 people in Germany, Italy, England, and North America. Production takes place exclusively at the German sites in Attendorn (headquarters), Radeberg and Ennest. However, to guarantee the worldwide availability of our aquatherm pipes at any time and to offer local, personal service, aquatherm works closely together with long-term partners and suppliers in about 70 countries around the globe.

The family business is now managed by Maik Rosenberg, son of aquatherm founder Gerhard Rosenberg, and Jan Kriedel.





AQUATHERM GREEN

Future-proof in all fields of application with individual solutions___

aquatherm has the solution for your challenge benefit from the versatile application possibilities of aquatherm green systems. Here you get an exemplary overview of the fields of application where you can

trust in aquatherm green. Yesterday. Today. Tomorrow.







Potable water

Abbreviations pipe structure:

multi-layer, fibre-reinforced

raised pressure resistance

UV-resistant

oxygen-tight

thermally insulated

hardly inflammable

polypropylene random copolymer

polypropylene random copolymer

with raised pressure resistance

polyethylene with raised temperatu-

industrial floor heating maritime applications

swimming pool technology

sports floor heating and cooling

Fields of applications:

000

<u>{{</u>*

fire protection sprinkler-systems	Diameter in mm
heating and cooling networks	SDR 7,4 MF
nousing and cooking notworks	SDR 7,4 MF UV
refrigeration	SDR 7,4 MF 01
connection heating and cooling	SDR 9 MF RI
ceiling heating and cooling	SDR 9 MF RI
certaing meaning and cooting	SDR 9 MF RI
surface heating and cooling	SDR 11 S
heating system construction	SDR 11 MF RI
industrial floor heating	SDR 11 MF RI

}	potable	water a	pplication	n

Lengths units in mm unless otherwise

weight data in kg/m

standard dimension ratio

packing unit

Pipe diameter ___

The diameter of the PP pipe determines its location and intended use. In order to be able to install a pipeline from the connection to the outlet, the pipe diameter of the individual pipes and fittings must be compatible with each other.

aquatherm green

Diameter	r in mm	16	17	20	25	32	40	50	63	75	90	110	125	160	200	250	315	355	400	450	500	630
SDR	6 S			0	0	0	0	0	0	0	0	0										-
SDR 7,	4 S			0	0	0	0	0	0								-					-
SDR 7,	4 MF			0	0	0											-					
SDR 7,	4 MF UV			0	0	0											-				-	
SDR 9	MF RP			-		0	0	0	0	0	0	0	0	0	0	0	0				-	
SDR 9	MF RP UV					0	0	0	0	0	0	0	0	0	0	0	0					
SDR 11	S			0	0	0	0	0	0	0	0	0	0	0	0	0	0		-	-		-

aquatherm blue

Diameter in mm	16	17	20	25	32	40	50	63	75	90	110	125	160	200	250	315	355	400	450	500	630
SDR 7,4 MF			0	0																	
SDR 7,4 MF UV			0	0											-				-		
SDR 7,4 MF OT			0	0							-			-	-				-		
SDR 9 MF RP					0																
SDR 9 MF RP UV			-		0						-										
SDR 9 MF RP OT					0																
SDR 11 S			0	0											-				-		
SDR 11 MF RP						0	0	0	0	0	0	0	0	0	0	0	0	0	0		
SDR 11 MF RP UV						0	0	0	0	0	0	0	0	0	0	0	0	0	0		
SDR 11 MF RP OT			-			0	0	0	0	0	0	0	0	0	0						
SDR 17,6 MF RP												0	0	0	0	0	0	0	0	0	0
SDR 17,6 MF RP UV												0	0	0	0	0	0	0	0	0	0

aquatherm energy green & blue


Diameter i	n mm	16	17	20	25	32	40	50	63	75	90	110	125	160	200	250	315	355	400	450	500	630
SDR 9	MF RP					0	0	0	0	0	0	0	0	0	0	0	0					
SDR 9	MF RP					0																
SDR 9	MF RP OT					0																
SDR 11	MF RP						0	0	0	0	0	0	0	0	0	0	0	0				
SDR 11	MF RP OT						0	0	0	0	0	0	0	0	0	0						
SDR 17,6	MF RP												0	0	0	0	0	0				

Fields of applications ___

Areas of application include heating system construction as well as refrigeration and air conditioning technology - you can find all areas of

	refrigeration	connection heating and cooling	heating system construction	maritime applications	swimming pool technology	sports floor heating and cooling	potable water
	*	<u> </u>	₩1		Ħ		Ŷ
aquatherm green				0	0		0
aquatherm blue	0	0	0	0	0	0	







12 Product types

AQUATHERM PRODUCT TYPES

Polypropylene pipe systems___

The history of the aquatherm pipe systems began in 1973 when Gerhard Rosenberg founded a company for hot water underfloor heating systems. Initially, the owner's garage and basement served as the company's headquarters and production facility. A lot has happened since then.

In the past 50 years, aquatherm has proven to be the world 's leading manufacturer of plastic pipe systems made of polypropylene for plant engineering and building services. The numerous product lines provide superior solutions in potable water applications, heating

systems, fire sprinkler systems, air conditioning and refrigeration technology, as well as in surface heating and cooling systems. The product range comprises almost 17,000 articles in six product lines.

Due to their special material properties, the aquatherm pipe systems convince by their diverse application possibilities.

The aquatherm pipe systems can be used in all areas of new installation, repair and renovation.

Characteristics

aquatherm polypropylene pipe systems stop corrosion damages. All materials are corrosion-resistant and have reduced flow noise compared to metallic pipes. aquatherm pipes are opaque, therefore there is no risk of algae formation.

Installation

aquatherm pipes and fittings are connected by heat fusion, which creates a homogeneous, cohesive unit with no leak paths. Heat fusion connections are stronger than the pipe itself, providing lasting safety at these critical points of a piping system. A properly executed aquatherm fusion creates a permanent leakproof connection. An aquatherm pipe with an outside diameter of 20 mm can be heat fused in only 5 seconds.

aquatherm pipe connections can be hydraulic pressure tested or put into operation directly after their fusion. There are no waiting times.



Quality ___


Quality is very important to aquatherm. This is not only reflected in the national and international certification marks, but also in the high satisfaction level of aquatherm customers, installers and engineers. You can find our international certificates here:

Warranty ___

Due to the high product quality, aquatherm offers a 10-year warranty on all pipes and fittings instead of the 2 years applicable under German law. The extended warranty period is covered by a comprehensive insurance policy from a leading insurance company in our industry. For details, see the Warranty section of this catalogue.

Price advantage ___

aquatherm offers you high quality, durable piping systems at an optima price/performance ratio.



PRODUCT TYPES

AQUATHERM GREEN

aquatherm green has revolutionized the plastic piping sector and has proven its technical suitability worldwide for decades. The innovative product family from aquatherm is made of corrosion-resistant, chemically inert polypropylene.

It is completely free of heavy metals and toxic chemicals and thus ideally suited for potable water applications. aquatherm green can also be used for swimming pools, agriculture or shipbuilding. It is joined by using reliable heat fusion, which eliminates the hazards of welding and creates virtually leak-free connections.

The system includes the different types of pipes SDR

6, SDR 7.4, SDR 9 and SDR 11. More than 450 joining and connection elements as well as valves and ball valves complete the system.

The products are available from 20 mm to 450 mm external diameter.

Fields of Applications

- O Potable water
- Swimming pool technology
- Maritime Applications

System components

The systems include all elements for the pipe system installation for chilled, hot fluid and various industrial applications.


Pipes in straight lengths and / or coils

- Fittings
- Flanged joints
- Water point connections and accessories
- Welding devices and machines
- Weld-in saddles
- Manifolds
- Shut-off devices
- Cutting and peeling tools
- Installation guide and fastenings
- Transition joints from PP to metal or from metal to PP

Diameter

The diameter of the PP pipe determines its location and intended use. In order to be able to lay a pipeline from the connection to the outlet, the pipe diameter of the individual pipes and fittings must be compatible

with each other. aquatherm green is available in the following diameters: 20, 25, 32, 40, 50, 63, 75, 90, 110, 125, 160, 200, 250, 315 mm



Standard dimention ratio (SDR)

The SDR (Standard Dimension Ratio) is a ratio indicating the resistance to pressure. In order to guarantee a certain pressure resistance, a certain maximum SDR number is necessary, depending on the type of material. The following applies: the greater the wall

thickness, the smaller the SDR number and the more pressure-resistant the plastic pipe. The unit indicates the ratio between outer diameter and wall thickness of a pipe. aquatherm green is available in the following SDR sizes:









SDR 9

SDR 11

PRODUCT TYPES

AQUATHERM GREEN - Overview

	SDR 6	SDR 7,4	SDR 9	SDR 11
aquatherm green S	0	0		0
S = single / single layer	ø: 20–110 mm	ø: 20–63 mm		ø: 20–315 mm
aquatherm green MF				
		0		
MF = multi-layer and fibre-reinforced composite pipe		ø: 20–32 mm 		
aquatherm green MF UV		0		
MF UV = multi-layer and fibre-reinforced com-				
posite pipe, UV-resistant		ø: 20–32 mm		
aquatherm green MF RP				
MEDD			0	
MF RP = multi-layer and fibre-reinforced com- posite pipe, raised pressure resistance			ø: 32–315 mm	
aquatherm green MF RP UV				
MF RP UV = multi-layer and fibre-reinforced composite pipe, raised pressure resistance,			0	
UV-resistant			ø: 32–315 mm	

AQUATHERM GREEN S__

Single-layer pipes are particularly suitable for use in cold water installations (medium temperature up to 25°C).



AQUATHERM GREEN MF RP

aquatherm green MF RP is a multilayer and fibrereinforced composite pipe and has an increased compressive strength.



AQUATHERM GREEN UV_

Pipes made of fusiolen® are normally not exposed to the effects of UV rays when installed. To bridge the transport and installation time, aquatherm polypropylene pipes and fittings are packed UV-protected. The maximum storage time outdoors is 6 months. For outdoor pipe installation, aquatherm offers polypropylene multilayer pipes with a UV-layer of polyethylene. This prevents the occurrence of damaging influences by sun rays.



UV-ADHESIVE TAPE

As an alternative to our polyproplylene pipes with UV protection layer, wrapping with UV-resistant adhesive tape is possible, if moulded parts or short pipe sections are to be protected. For this purpose, the adhesive tape recommended by aquatherm (art. no. 9700010871) should be selected, which shows good

resistance to abrasion, moisture, oils, light acids and alkalis as well as weather influences outdoors. The tape should always be applied to a dry, clean and grease-free surface. The winding should be done with a slight pull and at least 50% overlap.

18 Product types 19

AQUATHERM GREEN MF ___

aquatherm green MF is a multi-layer fibre-composite pipe. The pipe is made in a multi-layer extrusion process. The manufacturing process developed by aquatherm enables the integration of glass fibres within the material polypropylene in the middle layer of the pipe. This reinforces the pipe and restricts expansion and contraction.

 The linear expansion is reduced by at least 75 % compared with standard PP pipes.

The flow rate is increased by 20 % at the same pressure conditions due to smaller wall thicknesses.


High stability

The coefficient of linear expansion is nearly identical to that of metal pipes so that compared with usual plastic pipes the support intervals.

Lower weight

High impact rate

Simply cut and weld













Permissible working **pressure -** potable water ___

(Fluid transported: water according to DIN 2000)


cold potable water warm potable water

The determination of the allowable pressures resulted from the specific conditions to which pipe system components in the potable water domestic installation are exposed to.

Limiting factors such as increased flow rates, the use of disinfectants, increased content of oxygen, etc. were considered by the use of the appropriate safety factors.

For fittings of butt-welded pipe segments a reduction factor of 0.75 (reduction of the table values by 25 %) is effective.

Years of service	aquatherm green SDR 11 S	aquatherm green SDR 7.4 S	aquatherm green SDR 6 S	aquatherm green SDR 7.4 MF	aquatherm greer SDR 9 MF RF
at temper	ature up to 20 °	C (68 °F)			
1	15.0 bar	23.8 bar	30.0 bar	28.6 bar	25.0 ba
5	14.1 bar	22.3 bar	28.1 bar	26.8 bar	24.2 ba
10	13.7 bar	21.7 bar	27.3 bar	26.1 bar	23.9 ba
25	13.3 bar	21.1 bar	26.5 bar	25.3 bar	23.5 ba
50	12.9 bar	20.4 bar	25.7 bar	24.5 bar	23.1 ba
at tempera	ature up to 30 °	C (86 °F)			
1	12.8 bar	20.2 bar	25.5 bar	24.3 bar	21.7 ba
5	12.0 bar	19.0 bar	23.9 bar	22.8 bar	21.0 ba
10	11.6 bar	18.3 bar	23.1 bar	22.0 bar	20.6 ba
25	11.2 bar	17.7 bar	22.3 bar	21.3 bar	20.2 ba
50	10.9 bar	17.3 bar	21.8 bar	20.7 bar	19.9 ba
at tempera	ature up to 40 °	C (104 °F)			
1	-	17.1 bar	21.5 bar	20.5 bar	18.7 ba
5	-	16.0 bar	20.2 bar	19.2 bar	18.0 ba
10	-	15.6 bar	19.6 bar	18.7 bar	17.7 ba
25	-	15.0 bar	18.8 bar	18.0 bar	17.3 ba
50	_	14.5 bar	18.3 bar	17.5 bar	17.1 ba
at tempera	ature up to 50 °	C (122 °F)			
1	<u> </u>	14.5 bar	18.3 bar	17.5 bar	15.9 ba
5		13.5 bar	17.0 bar	16.2 bar	15.3 ba
10	_	13.1 bar	16.5 bar	15.7 bar	15.1 ba
25	_	12.6 bar	15.9 bar	15.2 bar	14.7 ba
50		12.2 bar	15.4 bar	14.7 bar	14.5 ba
at tempera	ature up to 60 °	C (140 °F)			
 1	<u> </u>	12.2 bar	15.4 bar	14.7 bar	13.5 ba
5		11.4 bar	14.3 bar	13.7 bar	13.0 ba
10	_	11.0 bar	13.8 bar	13.2 bar	12.7 ba
25		10.5 bar	13.3 bar	12.6 bar	12.4 ba
50	_	10.1 bar	12.7 bar	12.1 bar	12.2 ba
	ature up to 65 °				
1	-	11.6 bar	14.6 bar	13.9 bar	12.4 ba
5		10.8 bar	13.6 bar	12.9 bar	11.9 ba
10	_	10.4 bar	13.1 bar	12.5 bar	11.7 ba
25		10.0 bar	12.6 bar	12.0 bar	11.4 ba
50		8.8 bar	11.1 bar	10.6 bar	11.2 ba
	ature up to 70 °		11.1 bai	10.0 bai	11.2 04
1	-	10.3 bar	13.0 bar	12.4 bar	11.4 ba
5		9.5 bar	11.9 bar	11.4 bar	10.9 ba
10		9.3 bar	11.7 bar	11.4 bar	10.7 ba
25		8.0 bar	10.1 bar	9.6 bar	10.7 ba
30	-	7.0 bar	8.8 bar	9.6 bar 9.3 bar	
	-				10.3 ba
50	-	6.7 bar	8.5 bar	8.1 bar	10.2 ba





Material **fusiolen**®

Characteristics and special features

aquatherm green is made of corrosion-resistant material. This extends the service life of the hysical and chemical properties are the special requirements of the drinking water and heating heating sector. Due to the exceptionally welding properties, the pipe and fitting pipe and fitting merge into a homogeneous, cohesive unit.

This is what has made the material fusiolen® famous worldwide. known worldwide.



The advantages of aquatherm pipes and fusiolen® polypropylene

- corrosion resistant
- resistant against many chemicals
- high environmental compatibility
- O less pipe roughness
- heat and sound insulating characteristics
- very good welding properties

- O high heat-stabilised
- O high mechanical stability
- O lighter in weight than steel and copper
- O easy processing
- O well-priced
- installation aids and fixings

Our material fusiolen® Polypropylene

Decades of experience in the manufacture and use of PP-R/PP-RCT piping systems and the simultaneous striving for continuous further development have led to numerous improvements in aquatherm system technology.

Newly opened markets place ever increasing demands on the pipe material. Versatile applications require the greatest possible independence of the processed materials. Raw materials with novel properties that could not be achieved until then are required. For this reason, aquatherm has been developing and producing its own innovative polypropylene materials for several years, which meet the global challenges in sanitary and heating technology, in airconditioning and refrigeration technology, in industrial applications and agriculture, in shipbuilding and in fire protection.

Successful results of this research are fusiolen PP-R, fusiolen PP-RCT and fusiolen PP-R FS.

Environment

The environmentally friendly material polypropylen fusiolenR PP-R/PP-RCT is recyclable and can be ground, melted and reutilised for various applications e.g. motor-protections, wheel linings, laundry baskets and other kinds of transport boxes. There are no polluting substances with PP-R/PP-RCT either in its processing or in its disposal.

Use of metal deactivators

By adding suitable food-approved additives the risk of material damage caused by metal ions under extreme operating conditions is reduced.

Higher long-term heat stabilization

The long-term heat stabilization was increased in order to be able to counteract possible influences of the peak temperatures occurring during operation.

Material properties

Potable water is one of the most controlled commodity goods. The supply system should influence the water on its way up to the taps as less as possible. The choice of the right potable water pipe system and its material is of decisive importance. aquatherm green pipe systems are suitable for all different qualities of potable water.

The environmentally friendly and hygienically enhanced potable water pipe system made from fusiolenR is physiologically and microbiologically harmless. The technical suitability of the aquatherm pipe systems has been evident worldwide for decades. The extrapolated service life of aquatherm polypropylene pipes is more than 50 years.

Peak temperatures of 100 °C arising from short disruptions are unproblematic. Permanent temperatures from 70 °C up to 90 °C reduce the service life of the pipe (see table "Permissible Working Pressure", page 20–21).

When using aquatherm PP-R/PP-RCT pipes, the pressure and temperature conditions according to the table "Permissible workig pressure" apply. With regard to pressure and temperature, the operating conditions in the following table are to be used for pipes and pipe connections. These figures refer to potable water installations based on a theoretical service life of 50 years.

This is how aquatherm is **committed** ___

17 goals to change the world: In 2015, the global community developed the "Agenda 2030", a roadmap for the future.

This is intended to enable a dignified life world-wide and to preserve the natural foundations of life in the long term. We at aquatherm would like to contribute to the achievement of these goals with all our actions. Our sustainable products,

our comprehensive service and our leading expert knowledge are part of the solution on the way to a climate-neutral life.

We are also a member of the German Sustainable Building Council (DGNB e.V.) and work with the non-profit organisation to find ways and solutions to build for tomorrow today.

Climate change

back to content

Climate change is one of the greatest challenges of our time. Released CO_2 is the main problem: it enters the atmosphere and intensifies the greenhouse effect - the earth continues to heat up.

We are convinced that we humans will find solutions to meet this challenge and thus also significantly reduce CO₂ emissions in all sectors.

Construction industry

The construction industry is responsible for 36% of global energy consumption and 39% of energy- and process-related CO_2 emissions.*

The construction industry has already begun to face up to this responsibility. In order to achieve the final goal of a "net zero building" over the entire life cycle, the but the steps are still too small.

More courageous and visionary pioneers are needed, who will show the right way and set an example for the entire industry.

Exceptionally environmentally friendly __

The European Plastic Pipe Association TEPPFA analysed the environmental impact of plastic pipe systems as part of its EPD project. The result: plastic pipe systems have excellent environmental performance in various areas of application, leaving a smaller ecological footprint than pipe systems made of other materials.

A pipe system made of polypropylene (25 mm, SDR 7.4), for example, has approximately seven times lower CO_2 emissions than a comparable steel pipe.

Success through consistent **environmental protection** ___

We live environmental protection – and do so consistently. All corporate processes are geared to conserving valuable resources, minimising energy use, and avoiding or recycling waste.

We developed the first fibre composite pipe as early as 1999. This required significantly less energy in the production process than the conventional aluminium composite pipe.

Technical data sheet

Technical properties	fusiolen® PP-R	fusiolen® PP-R/ PP-RCT fibrepipe
Melt-flow index 190 °C/5 kg	0,5 g/10 min.	0,5 g/10 min.
Melt-flow index 230 °C/2.16 kg	0,3 g/10 min.	0,3 g/10 min.
Modulus of elasticity	800 N/mm ²	1200 N/mm²
Yield stress	25 N/mm ²	30 N/mm ²
Density	0.9 g/cm^3	$1,0~\mathrm{g/cm^3}$
Tensile strength	25 MPa	35 MPa
Inflammation temperature	430-450 °C	490-500 °C
Thermal expansion coefficient	1,5 *10 ⁻⁴ K ⁻¹	0.35 *10 ⁻⁴ K ⁻¹
Coefficient of thermal conduction	0,15 W/mK (measured at pipe)	0,15 W/mK (measured at pipe)
Coefficient of friction in pipes	0,007	0,007
Bending radius	6 x d	
Water absorption	< 0,02 %	< 0,02 %
Electrical properties	fusiolen® PP-R	fusiolen® PP-R/ PP-RCT fibrepipe

Electrical properties	fusiolen® PP-R	fusiolen® PP-R/ PP-RCT fibrepipe
Relative perwithtivity	2,3 (in case of 1 MHz)	2,3 (in case of 1 MHz)
Puncture voltage	500 kV/cm	500 kV/cm
Specific resistance	$> 10^{17}\;\Omega$ cm	$> 10^{17}\;\Omega$ cm
Surface resistance	$10^{14}~\Omega$	$10^{14}~\Omega$
Dissipation coefficient	0.0002 (in case of 50 Hertz)	0.0002 (in case of 50 Hertz)

Characteristics and special features

aquatherm Environmental Product Declaration ___

What is an **Environmental Product Declaration?**

An Environmental Product Declaration (EPD) describes the environmental impact of a product or service on the environment. It records the consumption of resources and emissions over the entire life cycle of the product - from the extraction of raw materials to disposal - and quantifies and evaluates them. Therefore, an Environmental Product Declaration offers the possibility to compare different products with each other.

In the Environmental Product Declaration, the characteristics of a product are identified neutrally using internationally recognised standards. A precise methodology according to ISO 14025 and EN 15804 is followed, and all values are checked by independent third parties regarding their completeness, plausibility, and conforwithy with standards.

However, the EPD is not a certificate, i.e. there are requirements placed on the quality and format of the data, but not on the quality of the product. For the building sector, it forms an important basis for the ecological assessment of buildings.

What are **product category rules?**

To be able to evaluate functionally similar products in the same way and in the context of an Environmental Product Declaration, Product Category Rules (PCRs) are used. These are a set of specific rules, requirements or guidelines according to which products are classified into groups. Product Category Rules exist, for example, for thermal insulation materials, windows and doors, or building piping systems.

What is a **Life Cycle Assessment?**

The aim of a Life Cycle Assessment (LCA) is not only to provide environmentally relevant data on specific products, but also to estimate potential environmental issues which then can assist in making a decision for or against a particular product. The basis of the Life Cycle Assessment is the life cycle of a product. It consists of different phases: Raw material extraction, material production, use, waste treatment and final disposal. All environmental inputs and outputs are listed. In other words, everything that flows into and out of the product is measured. These can be raw materials or resources, different types of energy, water or emissions into the air, soil or water.



What does the **Product life cycle include?**

Characteristics and special features

A life cycle assessment considers either the entire life cycle of a product or parts of it. Therefore, there are three different approaches to assessing the product life cycle:

What are the environmental impact indicators?

Life Cycle Assessments provide information on the potential impact of a product (or service) on the environment. EN 15804+A2 describes 13 core Environmental Impact Indicators to be reported for an Environmental Product Declaration and 6 additional optional Environmental Impact Indicators.

Core indicators according to EN 15804+A2:

Core indicator	Unit
GWP-total	kg $\mathrm{CO_2}$ -Äq.
GWP-fossil	kg $\mathrm{CO_2} ext{-}\mathrm{\ddot{A}q}$.
GWP-biogenic	kg $\mathrm{CO_2} ext{-}\mathrm{\ddot{A}q}$.
GWP-luluc	kg $\mathrm{CO_2} ext{-}\mathrm{\ddot{A}q}$.
ODP	kg CFC11-Äq.
AP	mol H⁺-Äq.
EP-freshwater	kg PO ₄ -Äq.
EP-marine	kg N-Äq.
EP-terrestrial	mol N-Äq.
POCP	kg NMVOC-Äq.
ADPE	kg Sb-Äq.
ADPF	MJ
WDP	m3 World-Äq. withdrawn

GWP = Global warming potential ODP = Stratospheric ozone depletion potential AP = Acidification potential of soil and water

sources - non-fossil resources (ADP substances

Additional impact categories according to EN 15804+A2-optional:

Indicator	Unit
PM	Illness cases
IR	kBq U235-Äq.
ETP-fw	CTUe
HTP-c	CTUh
HTP-nc	CTUh
SQP	-

U235

ETP-fw = Potential toxicity

HTP-c = Potential toxicity comparison unit for humans (carcinogenio

effect) HTP-nc = Potential toxicity

comparison unit for

comparison unit for humans (non-car-

cinogenic effect) Potential soil quality

ecosystems

How reliable is an **Environmental Product Declaration?**

Neutral and in accordance with internationally recognised standards: This is how the characteristics of a product are recorded in an Environmental Product Declaration. The exact methodology follows ISO 14025 and EN 15804, and all values are verified by independent third parties. The Environmental Product Declaration is valid for a period of five years. If there are changes in the manufacture of the product during this period, leading to major deviations from the previous values, a review must be carried out.

What advantages does the **Environmental Product Declaration offer me?**

Environmental Product Declarations enable companies, for example, to participate in public tenders or investors to have their building's sustainability systems, such as BREEAM, LEED or DGNB, in place. In addition, an Environmental Product Declaration forms the basis for the development and optimisation of sustainable products.

aquatherm **Environmental Product Declaration**

Environmental Product Declarations are important for the construction industry, for us, and our customers. That is why we have had our products evaluated according to the "cradle to gate" concept.

Our Environmental Product Declarations


are available for the following product group:

- aquatherm green/blue S/MF pipe
- aquatherm red pipe S/MF
- aquatherm black system
- aquatherm green/blue S/MF pipe (OT)
- aquatherm green/blue S/MF pipe (UV)
- aquatherm green/blue S/MF pipe (ENERGY)

Potential incidence of disease due to particulate matter EP = Eutrophication potential POCP = Potential for formation of tropospheric emissions. Potential effect from human exposure to

ozone
ADPE = Potential for depletion of abiotic re-

ADPF = Potential for depletion of abiotic resources - fossil fuels (ADP - fossil fuels)
WDP = Water depletion potential (users)



Fire protection ___

The aquatherm polypropylene pipe systems comply with the requirements of the fire classification B2 DIN 4102 (normal inflammable). Compared to natural products like wood, cork or wool, aquatherm PP-R pipes do not produce any gas toxicity. In case of fire, there is no risk of dioxin emissions.

To avoid fire and smoke transmission, aquatherm advises the use of fire retardant seals. The fire resistance period is the minimum period in minutes.

The extent of the preventive measures depends on the type of installation. The determination of fire areas and fire classification has to be made in accordance with the law of the country. Information is given by the Planning Department and Building Control Office or the Fire Protection Representative.

Basically, fire walls and ceilings with pipe passages have to be installed to the same fire resistance classification. All fire protection systems with a corresponding classification are suitable for aquatherm polypropylene pipes.

The following companies offer **suitable fire protection solutions:**

Fire protection pipe shell Conlit 150 U:


DEUTSCHE ROCKWOOL GmbH & Co. KG Rockwool Straße 37-41 45966 Gladbeck Tel: +49 2043 408 0 www.rockwool.de

Fire protection sleeve AWM II:


Flamro Brandschutz Vertriebs GmbH Am Sportplatz 2 56291 Leiningen Tel. +49 6746 9410-0 Mail: info@flamro.com www.flamro.de

Hilti Deutschland AG Hiltistrasse 2 · 86916 Kaufering Tel: +49 800 888 · www.hilti.de


Roku System AWM II in the wall




Roku System AWM II with synthesis rubber in the wall



Rockwool Conlit 150 U in the wall



Roku System AWM II in the ceiling



Roku System AWM II with synthesis rubber in the ceiling



Rockwool Conlit 150 U in the ceiling



Characteristics and special features

Excerpt from the **Rockwool planning and installation aid**

R 30- to R 90 pipe penetrations for the aquatherm installation systems with non-combustible media, such as drinking water, heating and cooling

Product name/ Material:

aquatherm green PP-R

SDR 6 S SDR 7.4 S **SDR 7.4 MF** SDR 7.4 MF UV SDR 11 S

aquatherm green PP-RCT

SDR 9 MF RP SDR 9 MF RP UV

aquatherm blue PP-R

SDR 7,4 MF SDR 7,4 MF OT SDR 7,4 MF UV SDR 11 S

aquatherm blue PP-RCT

SDR 9 MF RP SDR 9 MF RP OT SDR 9 MF RP UV SDR 11 MF RP SDR 11 MF RP OT SDR 11 MF RP UV

aquatherm red PP-R (B1)

SDR 7,4 MF HI

aquatherm black grid connection

aquatherm orange PE-RT

Components F 30 to F 90	F 30	F 60 F 90		
Solid ceiling Thickness minimum 150 mm	Conlit 150 U L ≥ 1000 mm	Conlit 150 U WD ²⁾ L ≥ 1000 mm	WD ²⁾	
Solid wall Thickness minimum 100 mm	Conlit 150 U L ≥ 1000 mm	Conlit 150 U WD ²⁾ L ≥ 1000 mm	WD ²⁾	
Light partition Thickness minimum 100 mm	Conlit 150 U L ≥ 1000 mm	Conlit 150 U WD ²⁾ L ≥ 1000 mm	WD ²⁾	ROCKWOOL 800/ Teclit PS Cold minimum thickness 30 mm

Variant according to ROCKWOOL abP P3726/4140MPA BS

System	Pipe dimension	Conlit 150 U			ROCKWOOL 800 ^{1), 2), 3)} TECLIT PS Cold ^{1), 2), 3)}			
	Outer diameter Da [mm]	GEG 50% ³⁾ d _/ d [mm]	Core drilling DK [mm]	GEG 100% ³⁾ d _/ /d [mm]	Core drilling DK [mm]			GEG 100 % ¹⁾ d _/ /d [mm]
	14,0	14/23	60	15/42,5	100	15/30	15/20	15/20
pipes without OT	16,0	16/22	60	16/42	100	18/30	18/20	18/20
or UV layer	17,0	17/21,5	60	18/41	100	18/30	18/20	18/20
aquatherm green	20,0	20/20	60	20/40	100	22/30	22/20	22/20
	25,0	25/17,5	60	25/37,5	100	28/30	28/20	28/20
aquatherm blue	26,0	26/17	60	28/51	130	28/30	28/20	28/20
aquatherm red	32,0	32/24	80	32/49	130	35/30	35/20	35/30
aquatherm grey	40,0	40/20	80	40/45	130	42/30	42/20	42/40
	50,0	50/25	100	50/50	150	54/30	54/30	54/40
aquatherm black	63,0	63/33,5	130	63/58,5	180	64/30	64/30	64/50
aquatherm orange	75,0	75/52,5	180	75/62,5	200	76/70	76/40	76/70
	90,0	90/65	220			102/30	102/40	102/80
	110,0	110/70	250			114/30	114/50	114/100
	16,0	18/21	60	18/41	100	18/20	18/20	18/20
	20,0	22/19	60	22/39	100	22/30	22/20	22/20
pipes without OT	25,0	27/16,5	60	28/51	130	28/30	28/20	28/20
or UV layer	32,0	34/23	80	35/47,5	130	35/30	35/20	35/30
aquatherm green	40,0	42/19	80	42/54	130	42/30	42/20	42/40
UV	50,0	53/23,5	100	54/53	160	54/30	54/30	54/40
aquatherm blue	63,0	64/33	180	64/58	180	76/30	76/30	76/50
OT + UV	75,0	71/51,5	180	76/62	200	89/30	89/40	89/70
- -	90,0	90/65	220			102/80	102/40	102/80
	110,0	113/53,5	220			114/30	114/50	114/100

Notes/special installation conditions

- Minimum insulation thickness required in conjunction with pipe penetration seals in accordance with abP P-3726/4140-MPA BS; thermal insulation
- requirements in accordance with GEG are also met.

 The insulation shell ROCKWOOL 800 or Teclit PS Cold can be used as additional insulation.
- For correct dimensioning of the insulation thickness for pipework with cold media, please follow the instructions in our Teclit cold insulation pipe and the insulation pipe
- In the area of escape routes, fire load encapsulation with ROCKWOOL 800 or Teclit PS Cold (insulation thickness: 30 mm) can be used.

All boundary conditions of the specified general building inspectorate test certificates (abP) or general type approvals (aBG) must be taken into account.

Fireload

The values required for determining the fire load within a fire section are calculated from the total of all flammable materials located within this area. The calculation for establishing the combustion heat V [kWh/m] for a fire section in the event of an outbreak is dependent on dimensions and materials. The basis used for the calculation of pipe systems made of polypropylene is the lower calorific value Hu = 12.2 kWh/kg (as per DIN V 18230 T1) in conjunction with the mass of material mpipe [kg/m]. The integrated layers of fibres in the aquatherm fibre composite pipes are also considered.


Depending on the calculation procedure, the fire load is worked out with reference to the burn-up factor. This value is designated as mfactor and is taken as 0.8 for polypropylene.

Combustion values V [kWh/m] for aquatherm green piping systems ____

Dimension mm	aquatherm green SDR 11 S	aquatherm green SDR 7,4 S	aquatherm green SDR 6 S	aquatherm green SDR 9 MF RP	aquatherm green SDR 7,4 MF
16	-	1,17	1,5	-	-
20	1,32	1,82	2,12	-	1,76
25	2,01	2,83	3,27	-	2,74
32	3,18	4,54	5,33	3,12	4,39
40	5,05	7,05	8,24	5,69	-
50	7,82	10,99	12,77	8,80	-
63	12,35	17,28	20,26	14,03	-
75	17,21	24,58	28,68	19,71	-
90	24,92	35,21	41,22	28,41	-
110	36,89	52,68	61,45	42,17	-
125	47,91	-	-	54,38	-
160	78,28	-	-	88,90	-
200	121,89	-	-	139,00	-
250	189,59	-	-	216,18	-
315	313,54	-	-	343,66	-
355	381,86	-	-	436,33	-
400	505,08	-	-	-	
450	639,28	-	-	-	-
500	-	-	-	-	-
630	-	-	-	-	-

Processing ___

There are many possibilities for the connection of aquatherm green piping systems. Whether welding or plugging: With the fusion techniques of aquatherm you quickly create a permanently tight connection.



Welding techniques

Due to their exceptionally good welding properties, pipe and fitting fuse to form a homogeneous, materially bonded unit. For this purpose, the pipe and fitting are briefly heated with the aid of tools provided for this purpose and then simply joined together; that's it! Double material thickness at the joint - this means double safety at the otherwise critical point of a piping system.

Socket welding

A safe and fast connection in the socket welding process is possible with our manual welder for pipes with dimensions of 20 to 63 mm.

➤ View video

Socket welding with welding machine

With pipe dimensions from 50 to 125 mm, our aquatherm welding machines ensure a safe and durable connection.

► View video

Butt welding

Large pipe dimensions from 160 to 630 mm are welded with special butt welding machines.

► View video

Electric welding jig

The aquatherm electrical welding jig facilitates the fusion of pipes with diameters of 63 to 125 mm.

► View video

Electric socket welding

Electric socket welding (heating coil welding) is suitable in hard-to-reach areas for pipes with dimensions of 20 to 250 mm. In this welding process, special sleeves with integrated heating wires are electrically heated and fused to the pipe.

► View video

Welding techniques for aquatherm blue OT____

Weld-in saddle OT

Branches in aquatherm blue OT can be easily produced with welding calipers, even subsequently. The use of shrink-wrapping calipers also reduces the amount of material and time.

► View video

Socket welding OT

A secure and quick connection for the oxygen-tight aquatherm blue pipe OT pipes in the dimensions 20 to 125 mm is possible using the socket welding method.

► View video

Push-fit technique

Push-fit fittings

Highest safety in a few minutes: This is offered by the new aquatherm push-fit fittings. Compared to the electro socket welding process, pipe connections can be made up to 40 % faster with the aquatherm push-in socket. In addition, the tooling requirement is significantly lower.

► View video



Characteristics and special features

Chemical and thermal disinfection ___

of aquatherm potable water systems made of polypropylene

a) Chemical disinfection of the system

Contrary to the disinfection of potable water, the disinfection of a system is a discontinuous measure, comprising a potable water system from the area of contamination to the tapping point of the consumer. In general, a disinfection is to be applied temporarily only in case of a proven contamination.

In case of discontinuous disinfections, it is allowed to load aquatherm pipes and the corresponding fittings twice a year with a content of free chlorine of 50 mg/l for not more than 12 hours. Alternatively, 150 mg/l hydrogen peroxide (H2O2) can be used for 24 hours. A temperature of 30 °C must not be exceeded during the disinfection process.

The use of a disinfection process, especially with chlorinated waters can have a direct influence on the lifetime of the potable water system. Under no circumstances should chlorine dioxide be used.

b) Chemical disinfection of potable water

In case of continuous disinfection with chlorinated potable water, it can be used with a content of free chlorine of up to 0.3 mg/l (liwith according to 2001 potable water ordinance). The maximum temperature of 70 °C should not be exceeded. Unless required by local regulations, residual disinfection is not necessary where there is no evidence of bacterial water contamination. Under no circumstances should chlorine dioxide be used.


Recommendation of the World Health Organization – Guidelines for potable water quality, fourth edition

For effective disinfection, there should be a residual concentration of free chlorine of $\geqslant 0.5$ mg/l after at least 30 min contact time at pH < 8.0. A

chlorine residual should be maintained throughout the distribution system. At the point of delivery, the minimum residual concentration of free chlorine should be $0.2 \, \text{mg/l}$.

c) Thermal disinfection of the system

In general, a thermal disinfection according to DVGW W551 is possible. In case of the thermal disinfection for the prevention of legionella bacteria according to DVGW worksheet W 551, the water temperature will be adjusted in such a way that it amounts to 70 °C for at least 3 minutes at all points of the potable water system. The maximum admissible liwiths of use regarding the service temperature and pressure are to be observed



Integration of other systems or components with aquatherm piping for pressure pipe applications ___

When integrating aquatherm piping systems with other systems or components not made of polypropylene (e.g. valves, pumps, other piping, check valves, strainers, etc), care must be taken to ensure the operating parameters for polypropylene won't damage the other materials or vice versa.

Be aware that even if the aquatherm pipe is compatible with the fluid being transported, other materials in the system may not be. All parts of the system must be verified as compatible with the medium being carried before installing them. And, while the aquatherm pipe does not require treatment

to protect it from corrosion, metals (ferrous and non-ferrous) in the system may be susceptible to corrosion.

Do not mix the aquatherm pipe with other piping systems in conditions that will cause the other system or components to fail.



Domestic hot water recirculation (DHWR)

A hot water circulation system includes all components that are in contact with the circulating water, including the flow and return supply. When there is copper piping used in conjunction with PP-R/PP-RCT in a DHWR system, care should be taken to ensure the operating conditions will not cause degradation or erosion/corrosion of the copper. aquatherm recommends following the Copper Development Association guidelines (CDA Publication A4015-14/16: The Copper Tube Handbook – www.copper.org) for sizing, temperature and flow velocity in copper tubing. This will also help ensure that the copper levels in the water do not approach the regulatory action levels recommended by independent institutions (e.g. U.S. Environmental Protection Agency (EPA), World Health Organization (WHO), Federal Ministry of Justice and Consumer Protection of Germany). Sustained high levels of copper in DHWR piping can damage components within the system, even PP-R.

Damage caused by copper in the water resulting from erosion/corrosion or other degradation of copper components in the DHWR system will void the aquatherm warranty.

Accordingly, and as mandated by various regulations and codes in DHWR systems, it is considered good design and operational practice to ensure that the maximum HW-temperature within any part of the system / loop does not exceed 60 °C (140 °F). Some regulations and codes further restrict the temperature at any fixture to a maximum of 50 °C (120 °F). There are some exceptions to this such as the process of thermal disinfection in health care facilities where temperatures of 70 °C (160 °F) or higher can be applied for short periods of time throughout the pipe system.

Importantly, the maximum temperature used must not exceed the rating of the pipe for the operating pressure. (See aquatherm green pipe catalogue -

table: permissible working pressure potable water -Fluid transported: water according to DIN 2000)

According to some regulations and codes, flow rates in a DHWR system should not exceed 0.5 m/s (1.5 ft/ sec) anywhere in the system, except in some special cases where velocities up to 1 m/s (3 ft/sec) are needed to achieve proper flow temperature. The CDA Publication A4015-14/16 - The Copper Tube Handbook - liwiths the velocity in DHWR system to similar rates. Permissible working pressure

When re-piping an existing DHWR-system originally installed in copper tubing, ensure all possible copper is replaced. If some copper remains as part of the system, strictly follow the rules and guidelines of the Copper Development Association (CDA Publication A4015-14/16: The Copper Tube Handbook) regarding flow rates and water conditions. Small amounts of copper or brass in valves and other equipment will generally not cause an issue. If the copper fails, it may degrade o-rings, gaskets, PP-R and other components as well, shortening their service life.

When adding PP-R/PP-RCT to an existing copper system in a DHWR-application, the level of copper in the water should be tested. These levels should not exceed 0.1 mg/L (ppm). Higher levels of total copper indicate that the copper pipe is corroding/eroding due to system and/or water conditions.

To hydraulically balance a DHWR-system and ensure the required flow rate for each area of the building, it is necessary to install hydraulic-balancing-valves in every circulating loop throughout the complete system. This also maintains the flow velocity in the smaller return piping at or below the manufacturer's or CDA's recommendations.

In addition to sizing the piping and pumps to the



correct flow velocity, care must also be taken to avoid water hammer and excessive surge pressures. Pump systems operating with on/off cycling, or pumps oversized for the piping, can create high pressure and fatique the piping material. The pump total dynamic head (TDH) must also be matched to the flow requirements, piping layout, and operating conditions to avoid cavitation for all components throughout the system.

Cavitation can lead to excessive system noise and more importantly, can result in the erosion and degradation of the pipe surface and other components. Properly sized variable-speed (VFD) constant pressure pumping systems and pressure-sustaining valves can alleviate these issues. The pumps should be sized to operate at maximum efficiency with the lowest energy usage for the required flow rate.

The issues described here are only of concern in DHWR-systems. For domestic cold water (DCW) and mechanical (heating-cooling)-systems no additional requirements or actions are necessary. In some situations, the DHWR system is also used to provide

hot water to the mechanical heating system. Additional consideration and care must be given for this type of combined system, as the mechanical components may not be compatible with the more aggressive water conditions and flow velocity liwithations of DHWR systems, and these components may be not suitable for potable water contact.

Certificates ___

Numerous international certificates testify to the high quality standard of the green pipes.

Some examples:

DVGW, SKZ, HIG (Germany)
AENOR (Spain)
ÖVGW (Austria)
WRAS (UK)
SAI-Global (Australia)
CSTB, CARSO (France)
SII (Israel)
TIN (Poland)
SITAC, KIWA, SWEDCERT (Sweden)

IIP (Italy) BRANZ (New Zealand)

CERTIF (Portugal)
EMI (Hungary)

u.v.m.

Hygienic suitability

According to DIN 1988 T2 all installation parts coming directly in contact with potable water are commodity goods according to the Law for Food and Commodity Goods. Plastic pipes have to comply with the KTW-recommendations of the Federal Public Health Department.

Material:


The hygienc suitability of the material used for the aquatherm green pipe system is independently verified through test certificates from the Hygienic Institute in Gelsenkirchen. The suitability for potable water pipes in the field of cold and hot water is confirmed by continuous tests.


Processing:

The joining method requires no additives such as fluxes or solder. The connection is made by socket fusion.

Potable water - our most precious commodity good:

The increasing use of PP in the field of food packing confirms the hygienic qualities of the material. This makes aquatherm green pipe the optimal packing for our most precious commodity good – potable water.





Comparison of the Water content per metre (L) _

Dimension mm	aquatherm green SDR 6 S	aquatherm green SDR 7,4 MF	aquatherm green SDR 9 MF RP	aquatherm green SDR 11 S
ø 20	0,137	0,163		0,206
ø 25	0,216	0,254		0,327
ø 32	0,353	0,423	0,483	0,539
ø 40	0,555	0,660	0,754	0,834
ø 50	0,876	1,029	1,182	1,307
ø 63	1,385	1,647	1,869	2,074
ø 75	1,963	2,323	2,659	2,959
ø 90	2,826	3,358	3,825	4,252
ø 110	4,229	4,999	5,725	6,359
ø 125			7,386	8,199
ø 160			12,109	13,430
ø 200			18,908	21,010
ø 250			29,605	32,861
ø 315			46,966	52,172
ø 355			59,625	66,325
ø 400				84,290
ø 450				106,477
ø 500				
ø 630				

back to content

 back to content
 back to content

 back to content

 back to content

 back to content

 back to content

 back to content

 back to content


 back to content

 back to content

 back to content

 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 conten

44





Fields of application




AQUATHERM GREEN FIELDS OF APPLICATION

Potable water ___


Impeccable potable water quality -Why you can rely on aquatherm products.

There are no stricter quality controls for any foodstuff than for potable water. Rightly so, because with no food we have more contact. aquatherm green offers you a corrosion-resistant, plasticiser-free, odourless and tasteless pipe system, with which you achieve a hygienically perfect water quality.

The fast and safe connection technology also ensures low installation costs. aquatherm also offers you solutions when it comes to drinking water distributors, chemical and thermal disinfection, underground potable water pipes and - in case of renovations mixed installations.









AQUATHERM QUALITY ASSURANCE

Quality "100 % Made in Germany" ___

To produce safe and innovative piping systems - that is the lived promise of aquatherm. This already starts with the raw material: We develop and refine our polypropylene granulate under the fusiolen® brand. This way we can always perfectly adjust the properties of our products to the requirements of the different fields of application. No matter whether its pipes or fittings: "100 % Made in Germany" applies to all of them. We produce exclusively and with the latest manufacturing technology at our German sites in Attendorn (headquarters), Ennest and Radeberg.

Only tested products then start their journey to our customers worldwide. In addition to the permanent in-house quality assurance, which includes the monitoring of testing equipment, process, production and incoming goods inspections as well as the final inspection, external monitoring is carried out by e.g. the Süddeutsche Kunststoffzentrum (SKZ), NSF (National Sanitation Foundation, USA), IIP (Instituto Italiano di Plastici, Italy), CSTB (Centre Scientifique et Technique du Bâtiment, France), TGM (Technologisches Gewerbemuseum, Austria) and the Hygieneinstitut des Ruhrgebiets. Numerous national and international neutral authorities and institutions confirm the high aquatherm quality standard.

Numerous national and international quality seals and approval certificates as well as our satisfied customers confirm again and again the high quality of our products.

Since 1996 aquatherm fulfills the requirements of the quality management system according to DIN ISO 9001.


This success is another step towards strengthening our competitive position and to meet the high requirements and the responsibility for our customers, partners and the environment.

See for yourself!



System ISO 9001:2015 ISO 14001:2015 ISO 50001:2018





Compliance with the system standard


You can find the overview of our international certificates here:

[♠] Certificate

b back to content

54





Heavierycae olibrerala counting response of the county of

AQUATHERM PLANNING SERVICES

Optimise the efficiency of your entire project workflow ___

ி Contact - Our experts for your request

Our team has many years of experience in the field of building services and is very familiar with the aquatherm product portfolio. Regular training ensures that our project planning is always up to date and that all legal regulations are implemented. This saves you the planning work and gives you significantly more time to concentrate on your core business.




AQUATHERM PLANNING SERVICES

What **planning services** does aquatherm offer? __

"Time is money" - a wisdom that proves true every day, especially in the construction industry. The sanitary, heating, and air-conditioning installations of any building project are always a time challenge, not only for architects and planners. The implementation on site often presents the executing site managers and installers with inconsiderable problems. If you choose aquatherm, you have a strong partner at your side who supports you before, during and after the completion of your project.

🕆 Digital planning tools on our websit



AQUATHERM PLANNING SERVICES

Pressure loss

For hydraulic pipeline calculations for the mathematical determination in pipe fittings, pressure loss coefficients are required. These result from friction, deflection and detachment losses. Losses often account for an inconsiderable proportion of the total pipe system.

The following table shows the calculated pressure loss coefficients or resistance coefficients for aquatherm fittings.

🕆 PDF Planning and design

back to content

58



60 References 61

AQUATHERM GREEN REFERENCES

Geothermal

Project

Gippsland Recreation and Aquatic Centre (GRAC

Location

Traralgon, Australia

Completion

202

Application


Geothermie

The challenge

For the new aquatic centre, a piping system was sought that was not only suitable for geothermal energy, but was also cor-rosion-resistant, durable, flexible and had good insulation properties.

The solution

Due to the special material properties, aquatherm green pipe in the dimensions 110 mm and 250 mm was selected and installed with technical support from aquatherm.











AQUATHERM GREEN REFERENCES

Potable water

Project

Riu Plaza de España

Location

Madrid, Spair

Completion

2019

Application

Potable water Refrigeration Sprinkler


The challenge

Fast and easy installation, safe and durable in operation: These were the piping system requirements that were desired in the rehabilitation of a historic tower in the areas of potable water, air conditioning piping and sprinklers.

The solution

Thanks to their special material properties three products from aquatherm were selected to ensure smooth installation and trouble-free operation in Riu Plaza de España.









AQUATHERM GREEN REFERENCES

Potable water ___

Project

Research vessels
"Snow Dragon 1" and "Snow Dragon 2"

Location

Shanghai, Chin

Completion

202

Application


Potable water Grey water Black water


The challenge

For the new construction of the "Snow Dragon 2," a corrosion-resistant piping system was sought for the areas of drinking water, grey water and black water


The solution

Products from aquatherm scored points due to their material properties and were used not only in the "Snow Dragon 2" but also in the sister ship "Snow Dragon 1" as a replacement for metal pipes.





Chemical resistance




AQUATHERM CHEMICAL RESISTANCE

Resistance__


Our corrosion-resistant material polypropylene is resistant to many acids and alkalis. However, each individual case must always be examined with special care. Chemical resistance must always be considered in conjunction with other factors such as operating temperature, operating pressure or external stresses. Detailed information is available from our competent team of experts, who will be happy to deal with individual enquiries.

ி Table "Chemical resistance"

♣ Formular Chemical resistance request"







aquatherm[®]

Explanatory comments on the aquatherm GmbH warranty ___

1. Foreword

Thank you very much for making the decision to use a product from aquatherm GmbH, Germany (herein referred to as "aquatherm"). With nearly 50 years of experience in the international plastic pipes market, and our trendsetting innovations, we have the expertise needed to offer you engineered piping solutions made in Germany.

The trust placed in the quality of our products has motivated us to offer all pipes and moulded, fabricated, machined, and/or assembled parts with a 10-year warranty instead of the standard 2-year warranty required by German law. This extended time covered by warranty is backed by a comprehensive insurance policy from a leading insurance company for our line of business. The warranty period will begin with the date of delivery by aquatherm GmbH, but only comes valid with the successful pressure test, which must be carried out and documented in accordance with the aquatherm specification.

2. Scope of warranty

The aquatherm warranty protects you from financial loss proven to be caused by material defects, manufacturing defects and/or aquatherm's consulting/engineering services. The warranty coverage shall apply for the following product groups:

- aquatherm green pipe (fusiotherm and aquatherm ISO)
- aquatherm blue pipe (climatherm and aquatherm ISO)
- aquatherm red pipe (firestop)
- aquatherm black system (climasystem)
- aquatherm lilac pipe (aquatherm lilac)
- aquatherm orange system (aquatherm heating systems)
- aquatherm grey pipe (aquatherm SHT-system)
- assemblies fabricated by aquatherm from these product groups

2.1 What is covered by the aquatherm warranty?

The aquatherm warranty covers three aspects of damages: property damage, financial loss and personal injury.

2.1.1 What is property damage?

The damage to or destruction of a tangible item as a result of a defective product (e.g. classic water damages as a result of a leak). As a result of this, the suitability of the tangible item to fulfill its actual purpose is impaired. The term property damage is used if tangible items are damaged or destroyed. Considerable costs can be incurred as a result of property damage, such as renovation costs, repair costs or replacement costs.

2.1.2 What is meant by financial loss?

Financial loss may either be out-of-pocket loss or loss of business. Out-of-pocket financial loss is for example the costs of removing products and installing replacements after damage. Loss of business is the financial disadvantage suffered by an injured party as a result of a dama-

ging event (e.g. lost income as a result of renovations following property damage).

2.1.3 What is meant by personal injury?

If a person suffers physical injury, this is known as personal injury. For the purposes of this document, the coverage of personal injury means the direct medical costs incurred as a result of the injury.

3. What is not covered?

Costs related to the damages incurred such as a result of:

- Non-compliance with the operating parameters defined and specified by aquatherm as found in aquatherm's technical documents. In cases of doubt, contact your local aquatherm manufacturer's rep. Exceptions must be provided for, in writing, by a member of aquatherm's engineering team.
- Non-compliance with the installation guidelines as set out in the aquatherm Catalogue, with emphasis to the required installation of aquatherm propriety clipping or other compatible with aquatherm piping.
- Non-compliance with respective National Plumbing Standards and Regulations.
- Joints which were not made in accordance with the aquatherm guidelines, including but not liwithed to: improper fusion technique, use of contaminated materials or tools, use of faulty or unsuitable tools, use of damaged materials or tools, or any connection made by an installer without sound knowlegde of the aquatherm connection techniques and their processes.
- Improperly assembled connections to other pipeline systems and/or components (threads, flanges, stubs, mechanical joints not intended for use with aquatherm PP piping etc.).
- All sealing elements used in the product lines manufactured by aquatherm
- Tools and accessories sold by aquatherm GmbH are covered for the warranty period by law under the statutory warranty provisions.
- Systems with defective pipeline sections or fittings that were not subjected to the aquatherm pressure test or alternative testing approved by aquatherm prior to start-up.
- Damage to our products caused by incorrect handling after the material has left aquatherm's possession.
- Damage caused or exacerbated by copper in the water resulting from erosion/corrosion or other degradation of copper components in a domestic hot water recirculating system.
- Time delay, caused by incorrect planning, delivery problems and/or incorrect orders.
- Damage caused by entrained air, cavitation and pressure fluctuations.

Note: This list only includes the most prominent examples. Other circumstances, which compromise the integrity of the products, may also jeopardise the coverage.

4. How is the amount of compensation under the aquatherm warranty determined?

In the event of a material failure, samples of the damaged/ faulty product are collected by the national aquatherm partner to forward them to aquatherm GmbH for examination and analysis. Working in collaboration with the injured party, aquatherm will identify the cause of the damage, and call in external bodies (test institutes, laboratories, assessors, etc.) as needed. If the damage has been caused by a material and/or manufacturing defect or by aquatherm's consulting/engineering services, the underwriter shall quantify the compensation claim for damages. All expenditures associated with the damages for this claim must be verified/recorded in detail and in a verifiable format as a required measure.

5. How much is the maximum coverage?

6. Why is the coverage stated in Euro?

The insured manufacturer, aquatherm, as well as the insurer, are both based in the EU, so that their agreements are issued in Euros (€). Since exchange rates fluctuate, the exchange rate current on the date of compensation shall apply.

7. What is the channel of communication for notifying claims under warranty and making enquiries about them?

Warranty claims have to be made to aquatherm via the national aquatherm GmbH partners. Information about the progress of the claim will only be released by the aquatherm partner or aquatherm GmbH.

8. Legal note

If a discrepancy or conflict arises between this document and the underlying insurance policy, the latter shall in all cases prevail.

9. Information about avoiding damage

Manufacture under certified quality level

As a trusted manufacturer, aquatherm works to a certified quality standard (ISO 9001); constant internal quality controls are part of the daily routine. In addition to this, all employees are integrated into a quality assurance program. As a result of this, products failing to comply

with our high standards are quickly identified and removed from our product range.

Preventing damage caused by incorrect handling

Our products must be handled conscientiously and carefully when they are delivered from our production plants. Experience shows that most damage is caused in transit, storage and/or when working on site. At this point we would draw close attention to the fact that correct handling contributes to maintaining the product quality.

II) Work is to be carried out by qualified installers

Installation defects are easy to avoid. Our training courses teach the correct techniques in detail for working with our products. In doing so, particular importance is attached to work being carried out attentively and with care. The work of installers trained by us or our aquatherm partners is much more reliable and carried out much more efficiently.

For a safe connection, we recommend using only aquatherm PP products in a piping system. Mixing with other PP piping systems should be avoided.

February 2023 aquatherm GmbH, Biggen 5, 57439 Attendorn, Germany

back to content

 content

 content

 content

 content

 content

 content

 content

 content

 content
 content

 content
 content

 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content

74



76 Transport and storage 7

AQUATHERM TRANSPORT AND STORAGE

Careful **storage**___

aquatherm polypropylene pipes may be stored outside at any temperature. A solid base for the pipe is very important to avoid a deformation of the pipes while in transport and storage.

At temperatures below 0 °C it is possible to damage the pipes through strong impacts. The material has to be treated with caution at low temperatures. In spite of its high resistance, aquatherm pipes should be treated with care. UV-radiation has effects on all high polymer plastics. Do not store permanently outdoor. The maximum permissible storage time outdoors is 6 months.



















Article list 81 Article list

Pipes / basic elements___



fusiolen® PP-R Material: aquatherm green SDR 6 / 7,4 S SDR 6 / S 2,5 & SDR 7,4 / S 3,2 Pine series: S = single / single layer DIN 8077 DIN 8078 Standards: DIN EN ISO 15874, ASTM F 2389, CSA B 137.11 Colour

Packing unit:

4 m straight lengths

l/mRG Article no. socket welding SDR 6 1011020006 20 3,4 13,2 0,137 0,174 12 100 1011025008 100 25 4,2 16,6 15 0,216 0,268 1011032010 32 5,4 21,2 0,353 0,437 20 1011040012 40 6,7 26,6 0,555 0,675 25 40 1011050014 50 32 8,3 33,4 0,876 1,047 20 1011063016 63 10,5 42,0 1,385 40 20 1,662 1011075018 75 50 12,5 5,0 1,963 2,351 20 1011090020 90 15,0 6,0 2,826 3,379 60 12 10111110022 110 18,3 73,4 4,229 5,040 65 100 1011016303 * 2,7 10,6 0,088 10 1011020306 3,4 13,2 0,137 0,174 12 100

SDR 7,4 1012020006 15 100 20 2,8 14,4 0,163 0,149 1012025008 0,254 100 25 3,5 18,0 0,232 20 1012032010 32 23,2 0,372 25 4,4 0,423 1012040012 40 5,5 29,0 0,660 0,578 32 40 1012050014 50 6,9 36,2 1,029 0,901 40 20 1012063016 1,647 1.416 50 63 8,6 45,8 20 12 100 1012016303 * 16 2,2 0,096 11,6 0,106 1012020306 * 14,4 15 100 20 2,8 0,163 0,149

0,216

0,268

15

100

16,6

Pipes / basic elements

aquatherm green SDR 7,4 MF UV

MF = multi-layer, fibre-reinforced

UV = UV-resistant

fusinlen® PP-R Material: SDR 7,4 / S 3,2 Pipe series: SK7 HR 3 28 ASTM F 2389 Standards: CSA B 137.11, ISO 21003, SKZ A314/616

Colour insdie green, outside black Packing unit: 4 m straight lengths

Article no.	d	S	di	l/m	kg/m	DN	PU	RG
socket welding								
1212020006	20	2,8	14,4	0,163	0,210	15	100	1
1212025008	25	3,5	18,0	0,254	0,314	20	100	1

aquatherm gre MF = multi-layer, fibre		Materi Pipe se Standa	eries:	fusiolen SDR 7,4 SKZ HR 3.28, ASTM F 2389 137.11, ISO 21003, SKZ AS					
			Colour: Packing unit:				green with 4 dark gree 4 m straigh		
Article no.	d	S	di	l/m	kg/m	DN	PU	RG	
socket welding									
1012020506	20	2,8	14,4	0,163	0,157	15	100	1	

0,254

0,244

18,0



25

3,5


MF = multi-layer, fibre-reinforced RP = raised pressure resistance

1012025508

fusiolen® PP-RCT Material: Pipe series: SDR 9 / S 4 SKZ HR 3.28, ASTM F 2389, Standards: ISO 21003. SKZ A632/A644 Colour: green with 4 dark green stripes Packing unit:

100

Ø 32 – 125 mm 4 m straight lengths Ø 160 - 315 mm 5,8 m straight lenghts











1011025308

*Packing unit: in ring


25

4,2

wall thickness in mm


DN

standard dimension ratio



Article list Article list 83

Pipes / basic elements___



aquatherm green SDR 9 MF RP UV

MF = multi-layer, fibre-reinforced RP = raised pressure resistance UV = UV-resistant

fusiolen® PP-RCT SDR 9 / S 4 SKZ HR 3.28, ASTM F 2389, Material: Pipe series: Standards: ISO 21003, SKZ A632/A644 inside green, outside black Colour: Packing unit: Ø 32 – 125 mm 4 m straight lengths
Ø 160 – 200 mm 5,8 m straight lengths

	W 16U - ZUU	mm 5,6 m	straight teng
DN	PI	Ú	RG

Article no.	d	s	di	l/m	kg/m	DN	PU	RG
socket welding								
1213032010	32	3,6	24,8	0,483	0,422	25	40	1
1213040012	40	4,5	31,0	0,754	0,630	32	40	1
1213050014	50	5,6	38,8	1,182	0,944	40	20	1
1213063016	63	7,1	48,8	1,869	1,457	50	20	1
1213075018	75	8,4	58,2	2,659	1,998	-	20	1
1213090020	90	10,1	69,8	3,825	2,894	65	12	1
1213110022	110	12,3	85,4	5,725	4,397	80	8	1
1213125024	125	14,0	97,0	7,386	5,530	100	4	1
butt welding								
1213160026	160	17,9	124,2	12,109	8,287	125	5,8	1
1213200028	200	22,4	155,2	18,908	12,818	150	5,8	1



aquatherm green SDR 11 S

S = single / single layer

fusiolen® PP-R SDR 11 / S 5 Material: Pipe series: DIN 8077 / 78, DIN EN ISO 15874, ASTM F 2389, CSA B 137.11 Standards: green with 4 blue stripes

Ø 32 – 125 mm 4 m straight lengths Ø 160 – 315 mm 5,8 m straight lenghts Packing unit:


Article no.	d	s	di	l/m	kg/m	DN	PU	RG
socket welding								
1014020006	20	1,9	16,2	0,206	0,108	15	100	1
1014025008	25	2,3	20,4	0,327	0,165	20	100	1
1014032010	32	2,9	26,2	0,539	0,261	25	40	1
1014040012	40	3,7	32,6	0,834	0,414	32	40	1
1014050014	50	4,6	40,8	1,307	0,641	40	20	1
1014063016	63	5,8	51,4	2,074	1,012	50	20	1
1014075018	75	6,8	61,4	2,959	1,411	65	20	1
1014090020	90	8,2	73,6	4,252	2,043	80	12	1
1014110022	110	10,0	9,0	6,359	3,026	-	8	1
1014125024	125	11,4	102,2	8,199	3,924	100	4	1
1014020306 *	20	1,9	16,2	0,206	0,108	15	100	1
1014025308 *	25	2,3	20,4	0,327	0,165	20	100	1
1014032310 *	32	2,9	26,2	0,539	0,261	25	50	1
butt welding								
1014160026	160	14,6	130,8	13,430	6,415	125	5,8	1
1014200028	200	18,2	163,6	21,010	9,992	150	5,8	1
1014250030	250	22,7	204,6	32,861	15,548	200	5,8	1
1014315032	315	28,6	257,8	52,172	24,664	250	5,8	1
*Packing unit in ring								

Socket___


Socket SDR 6 / 7,4 / 9 / 11 / 17,6			St	aterial: andards: blour:	DIN 169	fusiolen® PP 62, DIN EN ISO 158 gre	
Article no.	d	D	L	Z	kg	PU	RG
socket welding							
1040020002	20	27,0	32,0	3,0	0,008	10	1
1040025003	25	34,0	35,0	3,0	0,013	10	1
1040032004	32	43,0	40,5	4,5	0,026	5	1
1040040005	40	52,0	47,5	6,5	0,044	5	1
1040050006	50	68,0	53,0	6,0	0,084	5	1
1040063007	63	84,0	60,5	5,5	0,139	1	1
1040075008	75	100,0	66,5	6,5	0,226	1	1
1040090009	90	120,0	72,5	6,5	0,343	1	1
1040110010	110	147,0	82,0	8,0	0,581	1	1
1040125011	125	167,0	92,0	12,0	0,845	1	1

 	
d -	
	_
	_


Electrofusion so SDR 6 / 7,4 / 9 / 11 / 17,6					Material: Standards: Colour:	fusiolen® PP- DIN 16962, DIN EN ISO 1587 gree		
Article no.	d	D	L	h	kg	PU	RG	
socket welding								
1040020094	20	31,5	70,0	36,0	0,049	1	1	
1040025100	25	36,5	78,0	38,5	0,057	1	1	
1040032101	32	45,0	80,0	42,5	0,077	1	1	
1040040102	40	54,0	92,0	47,0	0,103	1	1	
1040050103	50	65,0	103,0	52,0	0,142	1	1	
1040063104	63	81,5	118,0	58,0	0,239	1	1	
1040075105	75	96,0	130,0	64,5	0,347	1	1	
1040090106	90	113,5	145,0	72,0	0,501	1	1	
1040110107	110	139,0	160,0	82,5	0,821	1	1	
1040125108	125	156,0	172,0	90,0	1,097	1	1	
1040160109 *	160	197,0	186,0	109,5	1,754	1	1	
1040200110 *	200	243,0	210,0	134,0	3,625	1	1	
1040250111 *	250	315,0	250,0	170,0	7,142	1	1	




l	n				fusiolen® P DIN 16962, DIN EN ISO 15 gr		
	D	Z	kg	PU	RG		
25,5	27,0	11,0	0,013	10	1		
29,5	34,0	13,5	0,023	10	1		
35,0	43,0	17,0	0,043	5	1		
41,5	52,0	21,0	0,077	5	1		
49,5	68,0	26,0	0,162	5	1		
60,0	84,0	32,5	0,293	1	1		
68,5	100,0	38,5	0,445	1	1		
79,0	120,0	46,0	0,729	1	1		
93,0	147,0	56,0	1,292	1	1		
116,5	167,0	76,5	2,004	1	1		
	29.5 2 35.0 41.5 49.5 6 60.0 6 68.5 79.0 93.0	29.5 34.0 29.5 35.0 43.0 41.5 52.0 49.5 68.0 60.0 84.0 66.5 100.0 79.0 120.0 93.0 147.0	29,5 34,0 13,5 2 35,0 43,0 17,0 1 41,5 52,0 21,0 4 49,5 68,0 26,0 8 60,0 84,0 32,5 6 68,5 100,0 38,5 1 79,0 120,0 46,0 93,0 147,0 56,0	34,0 13,5 0,023 2,0 35,0 43,0 17,0 0,043 3,0 41,5 52,0 21,0 0,077 49,5 68,0 26,0 0,162 6,0 84,0 32,5 0,293 6,6 100,0 38,5 0,445 7,0 120,0 46,0 0,729 1,7,0 147,0 56,0 1,292	29,5 34,0 13,5 0,023 10 2 35,0 43,0 17,0 0,043 5 3 41,5 52,0 21,0 0,077 5 49,5 68,0 26,0 0,162 5 66,0 84,0 32,5 0,293 1 66,5 100,0 38,5 0,445 1 79,0 120,0 46,0 0,729 1 93,0 147,0 56,0 1,292 1		



Elbow__



Elbow 90° inside / SDR 6/7,4/9/11	Material: Standards: Colour:			fusiolen® PP DIN 16962, DIN EN ISO 158 gre						
Article no.	d	l	l1	D	Z	z1	kg	PU	RG	
socket welding										
1080020061	20	25,5	25,5	27,0	11,0	13,5	0,032	10	1	
1080025062	25	29,5	29,5	34,0	13,5	17,0	0,023	10	1	
1080032063	32	35,0	39,0	43,0	17,0	21,5	0,048	5	1	
1080040064	40	41,5	45,5	52,0	21,0	26,0	0,080	5	1	




Elbow 90° butt welding			Material: Standards: Colour:	-	fusiolen® PP-R / PI DIN 16962, DIN EN ISO 1	
Article no.	D	Z	kg	PU	RG	
butt welding						
SDR 9						
1083160070 *	160,0	145,0	2,371	1	1	
1083200071 *	200,0	209,0	4,320	1	1	
1083250072 *	250,0	240,0	8,500	1	1	
SDR 11						
1084160052 *	160,0	145,0	1,956	1	1	
1084200054 *	200,0	209,0	4,575	1	1	
1084250056 *	250,0	240,0	7,180	1	1	
*Injection moulded part						

*Injection moulded part

Please note! Electrofusion sockets cannot be processed directly with injection moulded parts. When using electrofusion sockets, either segment welded special fittings must be used or pipe sections must be welded to the injection moulded fittings.


Segment welded article



Elbow 45° soc SDR 6 / 7,4 / 9 / 11 /		g		Material: Standards: Colour:	DIN 169	fusiolen® PF 762, DIN EN ISO 158 gre	
Article no.	d	l	D	Z	kg	PU	RG
socket welding							
1080020002	20	19,5	29,5	5,0	0,014	10	1
1080025003	25	22	34,0	6,0	0,018	10	1
1080032004	32	25	43,0	7,5	0,035	5	1
1080040005	40	30	52,0	9,5	0,053	5	1
1080050006	50	35	68,0	11,5	0,112	5	1
1080063007	63	41,5	84,0	14,0	0,227	1	1
1080075008	75	46,5	100,0	16,5	0,350	1	1
1080090009	90	52,5	120,0	19,5	0,568	1	1
1080110010	110	60,5	147,0	23,5	1,025	1	1
1080125011	125	67	167,0	27,0	1,329	1	1

Elbow__


Elbow 45° ir SDR 6 / 7,4 / 9 / 11) S	DI	fusiole DIN 16962, DIN EN IS						
Article no.	d	l	l1	D	Z	z1	kg	PU	RG	
socket welding										
1080020020	20	19,5	19,5	29,5	5,0	9,0	0,013	10	1	
1080020021	25	22,0	22,0	34,0	6,0	8,5	0,017	10	1	
1080032022	32	25,5	29,0	43,0	7,5	11,5	0,036	5	1	
1080040023	40	3N N	33 U	52 N	9 5	13.5	0.057	5	1	




Elbow 45° butt w segment welded* (or injecti	•	Material: Standards: Colour:	DIN	fusiolen® PP-F 16962, DIN EN ISO 158 gre	
Article no.	D	Z	kg	PU	RG
butt welding					
SDR 9					
1083160030	160,0	95,0	4,230	1	1
1083200031	200,0	146,0	7,500	1	1
1083250032	250,0	182,0	17,000	1	1
1083315033 *	315,0	498,0	30,567	1	1
SDR 11					
1084160013	160,0	95,0	1,371	1	1
1084200015	200,0	146,0	3,310	1	1
1084250017	250,0	182,0	6,218	1	1
1084315018 *	315,0	498,0	27,300	1	1
*					

*segment welded


Please note! Electrofusion sockets cannot be used with injection moulded parts. When using electrofusion sockets, welded special moulded parts must be used.






Segment welded article

T-piece__






T-piece sock SDR 6 / 7,4 / 9 / 11		•	d fittings	St	aterial: tandards: olour:	fusio DIN 16962, DIN EN			n® PP 30 158 gre	
Article no.	d	l	D	L	Z	z1	kg	PU	RG	
socket welding										
1060020016	20	25,5	27,0	51,0	11,0	11,0	0,017	10	1	
1060025017	25	30,5	34,0	62,0	14,5	15,0	0,033	10	1	
1060032018	32	33,5	43,0	70,0	15,5	17,0	0,054	5	1	
1060040019	40	40,5	52,0	81,0	20,0	20,0	0,099	5	1	
1060050020	50	49,5	68,0	99,0	26,0	26,0	0,177	5	1	
1060063021	63	60,0	84,0	120,0	32,5	32,5	0,368	1	1	
1060075022	75	68,5	100,0	137,0	38,5	38,5	0,541	1	1	
1060090023	90	79,0	120,0	158,0	46,0	46,0	0,920	1	1	
1060110024	110	93,0	147,0	186,0	56,0	56,0	1,598	1	1	
1060125025	125	116,5	167,0	233,0	76,5	76,5	2,673	1	1	



Injection moulded part





Segment welded article


T-piece butt we	elding		Material: Standards: Colour:	DIN 16	fusiolen® PP-R 962, DIN EN ISO 158 gre	
Article no.	D	L	Z	kg	PU	RG
butt welding						
SDR 9						
1063160019	160,0	290,0	145,0	3,290	1	1
1063200020	200,0	410,0	205,0	7,000	1	1
1063250021	250,0	486,0	243,0	12,500	1	1
1063315022 *	315,0	920,0	460,0	42,609	1	1
SDR 11						
1064160013	160,0	290,0	145,0	2,943	1	1
1064200015	200,0	410,0	205,0	6,099	1	1
1064250017	250,0	486,0	243,0	10,710	1	1
1064315018 *	315,0	920,0	460,0	20,450	1	1
*seament welded						

*segment welde

Please note! Electrofusion sockets cannot be used with injection moulded parts. When using electrofusion sockets, welded special moulded parts must be used.

T-piece__

led. T-pi DR 6 / 7,4 / 9				•		gs			Stand Colou			DIN 16	5962, I	DIN E
rticle no.	d	d1	d2	l	l1	D	D1	L	Z	z1	z2	kg	PU	RG
ocket welding														
060020030	20	16,0	16,0	25,5	25,3	29,5	29,5	51,0	11,0	12,3	12,5	0,025	10	1
060020031	20	16,0	20,0	25,5	25,3	29,5	29,5	51,0	11,0	12,3	11,0	0,024	10	1
060020032	20	20,0	16,0	25,5	25,3	29,5	29,5	51,0	11,0	10,8	12,5	0,023	10	1
060020033	20	25,0	20,0	31,0	30,5	34,0	34,0	62,0	16,5	14,5	16,5	0,040	10	1
060025034	25	16,0	16,0	31,0	30,5	34,0	34,0	62,0	15,0	17,5	18,0	0,043	10	1
060025035	25	16,0	20,0	31,0	30,5	34,0	34,0	62,0	15,0	17,5	16,5	0,041	10	1
060025036	25	16,0	25,0	31,0	30,5	34,0	34,0	62,0	15,0	17,5	15,0	0,038	10	1
060025037	25	20,0	20,0	31,0	30,5	34,0	34,0	62,0	15,0	16,0	16,5	0,039	10	1
060025038	25	20,0	25,0	31,0	30,5	34,0	34,0	62,0	15,0	16,0	15,0	0,036	10	1
060032039	32	16,0	32,0	35,0	31,0	43,0	29,5	70,0	17,0	18,0	17,0	0,053	5	1
060032040	32	20,0	20,0	36,8	37,0	43,0	43,0	73,5	18,8	22,5	22,3	0,076	5	1
060032041	32	20,0	32,0	35,0	31,0	43,0	29,5	70,0	17,0	16,5	17,0	0,053	5	1
060032042	32	25,0	25,0	35,0	34,5	43,0	43,0	70,0	17,0	18,5	19,0	0,069	5	1
060032043	32	25,0	32,0	35,0	32,0	43,0	34,0	70,0	17,0	16,0	17,0	0,050	5	1
060040044	40	20,0	40,0	41,5	36,0	52,0	34,0	83,0	21,0	21,5	21,0	0,091	5	1
060040045	40	25,0	40,0	41,5	36,0	52,0	34,0	83,0	21,0	20,0	21,0	0,089	5	1
060040046	40	32,0	40,0	42,0	40,5	52,0	52,0	84,0	21,5	22,5	21,5	0,092	5	1
060050047	50	20,0	50,0	49,5	40,5	68,0	29,5	99,0	26,0	26,0	26,0	0,162	5	1
060050048	50	25,0	50,0	49,5	44,5	68,0	34,0	99,0	26,0	28,5	26,0	0,158	5	1
060050049	50	32,0	50,0	49,5	44,5	68,0	43,0	99,0	26,0	26,5	26,0	0,160	5	1
060050050	50	40,0	50,0	49,5	49,5	68,0	68,0	99,0	26,0	29,0	26,0	0,161	5	1
060063051	63	20,0	63,0	60,0	48,5	84,0	34,0	120,0	32,5	34,0	32,5	0,335	1	1
060063052	63	25,0	63,0	60,0	48,5	84,0	34,0	120,0	32,5	32,5	32,5	0,331	1	1
060063053	63	32,0	63,0	60,0	53,0	84,0	52,0	120,0	32,5	35,5	32,5	0,340	1	1
060063054	63	40,0	63,0	60,0	53,0	84,0	52,0	120,0	32,5	33,0	32,5	0,332	1	1
060063055	63	50,0	63,0	60,0	56,0	84,0	68,0	120,0	32,5	36,5	32,5	0,398	1	1
060075056	75	20.0	75,0	68,5	54,5	100,0	34,0	137,0	38,5	40.0	38,5	0,501	1	1
060075057	75	25,0	75,0	68,5	54,5	100,0	34,0	137,0	38,5	38,5	-	0,497	1	1
060075058	75	32,0	75,0	68,5	59,0	100,0	52,0	137,0	38,5	41,0	38,5	0,505	1	1
060075059	75	40,0	75,0	68,5	59,0	100,0	52,0	137,0	38,5	38,5	38,5	0,497	1	1
060075060	75	50,0	75,0	68,5	66,0	100,0	84,0	137,0	38,5	42,5	38,5	0,550	1	1
060075061	75	63,0	75,0	68,5	66,0	100,0	84,0	137,0	38,5	38,5	38,5	0,515	1	1
060090062	90	32,0	90,0	79,0	64,0	120,0	43,0	158,0	46,0	46,0	46,0	0,880	1	1
060090063	90	40,0	90,0	79,0	66,5	120,0	52,0	158,0	46,0	46,0	46,0	0,862	1	1
060090064	90	50,0	90,0	79,0	69,5	120,0	68,0	158,0	46,0	46,0	46,0	0,905	1	1
060090065	90	63,0	90,0	79,0	73,5	120,0	84,0	158,0	46,0	46,0	46,0	0,876	1	1
060090066	90	75,0	90,0	79,0	76,0	120,0	100	158,0	46,0	46,0	46,0	0,991	1	1
060110067	110	63,0	110,0	93,0	83,5	147,0	84,0	186,0	56,0	56,0	56,0	1,534	1	1
060110068	110	75,0	110,0	93,0	86,0	147,0	100,0	186,0	56,0	56,0	56,0	1,517	1	1
060110069	110	90,0	110,0	93,0	89,0	147,0	120,0	186,0	56,0	56,0	56,0	1,548	1	1
060125070	125	75,0	125,0	116,5	106,5	167,0	100,0	233,0	76,5	76,5	76,5		1	1
060125070	125	90,0	125,0	116,5	100,5	167,0	120,0	233,0	76,5	76,5	76,5	2,509	1	' 1
0001230/I	123	70,0	123,0	110,3	107,3	107,0	120,0	200,0	70,3	, 0,3	70,3	2,307	_ '	- 1






fusiolen® PP-R / PP-RCT


Material:


T-piece ___



Please note! Electrofusion sockets cannot be used with injection moulded parts. When using electrofusion sockets, welded special moulded parts must be used.

*MF = multi-layer, fibre-reinforced







Red. T-piece bu	itt welding	l			Material: Standards: Colour:	DIN 169	fusiolen® PP-1 962, DIN EN ISO 150 gr
Article no.	D	D1	L	Z	kg	PU	RG
Depature: butt welding							
SDR 9							
1063200126	200,0	160	500,0	300,0	9,332	1	1
1063250131	250,0	160	750,0	375,0	21,547	1	1
1063250132	250,0	200	750,0	376,0	21,853	1	1
1063315134 *	315,0	160	920,0	238,0	29,237	1	1
1063315135	315,0	200	920,0	460,0	42,166	1	1
1063315136	315,0	250	920,0	460,0	42,557	1	1
SDR 11							
1064200088	200,0	160	500,0	300,0	7,445	1	1
1064250098	250,0	160	750,0	375,0	19,500	1	1
1064250100	250,0	200	750,0	375,0	18,500	1	1
1064315102 *	315,0	160	920,0	237,5	24,850	1	1
1064315103	315,0	200	920,0	460,0	29,400	1	1
1064315104	315,0	250	920,0	460,0	30,500	1	1
*Pipe with weld-in saddle							

Crosspiece, cross-over fitting, end caps___


Crosspiece SDR 6 / 7,4 / 9 / 11				S	faterial: tandards: olour:	DIN 169	fusiolen® PP 62, DIN EN ISO 158 gree
Article no.	d	D	L	Z	kg	PU	RG
socket welding							
1040020090	20	29,5	51,5	11,3	0,025	10	1
1040025091	25	34,0	59,0	13,5	0,035	10	1
1040032092	32	43,0	70,0	17,0	0,062	5	1
1040040093	40	52,0	83,0	21,0	0,099	5	1




Cross-over fitting SDR 6/7.4/9/11				Material: Standards: Colour:	DIN 16	fusiolen® 962, DIN EN ISO 1 g	
Article no.	d	L	h	kg	PU	RG	
socket welding							
1090020002	20	352,0	32,0	0,060	10	1	
1090025003	25	352,0	37,5	0,091	10	1	
1090032004	32	352,0	48,0	0,154	5	1	




End caps SDR 6 / 7,4 / 9 / 11				Mate Stand Color	dards:	DIN 1696	fusiolen® PP-R 2, DIN EN ISO 15874 green
Article no.	d	D	L	Z	kg	PU	RG
socket welding							
1020020002	20	29,5	24,0	9,5	0,009	10	1
1020025003	25	34,0	24,0	8,0	0,011	10	1
1020032004	32	43,0	29,0	11,0	0,023	5	1
1020040005	40	52,0	38,0	17,5	0,042	5	1
1020050006	50	68,0	44,5	21,0	0,082	5	1
1020063007	63	84,0	52,0	24,5	0,146	1	1
1020075008	75	100,0	58,5	28,5	0,243	1	1
1020090009	90	120,0	67,5	34,5	0,365	1	1
1020110010	110	147,0	65,0	28,0	0,635	1	1
1020125011	125	167,0	82,0	42,0	0,872	1	1




Crosspiece, cross-over fitting, end caps___






End caps but	t welding				Material: Standards: Colour:	DIN 16	fusiolen® 962, DIN EN IS
Article no.	d	D	L	Z	kg	PU	RG
butt welding							
SDR 9							
1023160022	124,2	160,0	70,0	17,9	0,847	1	1
1023200023	155,2	200,0	80,0	22,4	1,373	1	1
1023250024	194,2	250,0	90,0	27,9	2,856	1	1
1023315025	244,6	315,0	70,0	52,5	5,080	1	1
1023355026	275,6	355,0	80,0	66,5	7,050	1	1
SDR 11							
1024160013	130,8	160,0	70,0	14,6	0,631	1	1
1024200015	163,6	200,0	80,0	18,2	1,070	1	1
1024250017	204,6	250,0	90,0	22,7	1,989	1	1
1024315018	257,8	315,0	70,0	52,5	4,200	1	1
1024355019	290,6	355,0	80,0	67,5	6,410	1	1
1024400020	327,4	400,0	70,0	60,0	7,190	1	1
1024450021	368,2	450,0	80,0	70,0	10,500	1	1




Transition SDR 6 / 7,4 / 1		ece wi	th mal	e threa	ıd		Materi Standa Colour	ards:	DIN			R / brass SO 15874 green
Article no.	d	l	l1	D	D1	z2	R	Z	kg	PU	RG	
socket welding												
1060020154	20	31,5	53,0	29,5	37,0	16,0	1/2"	17,0	0,102	10	1	

Reducing piece___

Reducing p SDR 6 / 7,4 / 9 / 1		ILKEL W	ecully				Material: Standards: Colour:		DIN 16962	2, DIN EN IS	0 1581 gre
Article no.	d	d1	d2	l	D	L	Z	kg	PU	RG	
socket welding											
1040020020	20	16,0	13,5	14,5	24,5	39,0	11,5	0,009	10	1	
1040025021	25	16,0	16,5	16,0	26,0	38,0	9,0	0,012	10	1	
1040025022	25	20,0	16,5	16,0	29,5	38,5	8,0	0,012	10	1	
1040032023	32	20,0	21,5	18,0	29,5	37,5	5,0	0,015	5	1	
1040032024	32	25,0	21,0	18,0	34,0	38,0	4,0	0,016	5	1	
1040040025	40	20,0	26,5	20,5	29,5	45,0	10,0	0,025	5	1	
1040040026	40	25,0	26,5	20,5	34,0	50,0	13,5	0,028	5	1	
1040040027	40	32,0	26,5	20,5	43,0	50,0	11,5	0,032	5	1	
1040050028	50	20,0	33,5	23,5	29,5	55,0	17,0	0,045	5	1	
1040050029	50	25,0	33,5	23,5	34,0	55,0	15,5	0,044	5	1	
1040050030	50	32,0	33,5	23,5	43,0	54,0	12,5	0,048	5	1	
1040050031	50	40,0	33,5	23,5	52,0	53,0	9,0	0,053	5	1	
1040063032	63	20,0	42,0	27,5	29,5	65,0	23,0	0,073	1	1	
1040063033	63	25,0	42,0	27,5	34,0	65,0	21,5	0,071	1	1	
1040063034	63	32,0	42,0	27,5	43,0	62,0	16,5	0,080	1	1	
1040063035	63	40,0	42,0	27,5	52,0	64,5	16,5	0,089	1	1	
1040063036	63	50,0	42,0	27,5	68,0	63,5	12,5	0,107	1	1	
1040075037	75	40,0	50,0	30,0	52,0	69,5	19,0	0,131	1	1	
1040075038	75	50,0	50,0	30,0	68,0	63,0	9,5	0,141	1	1	
1040075039	75	63,0	50,0	30,0	84,0	71,0	13,5	0,170	1	1	
1040075040	75	20,0	50,0	30,0	34,5	65,5	21,0	0,113	1	1	
1040075041	75	25,0	50,0	30,0	34,5	65,5	19,5	0,111	1	1	
1040075042	75	32,0	50,0	30,0	52,0	69,5	21,5	0,140	1	1	
1040090043	90	50,0	60,0	33,0	68,0	75,0	18,5	0,193	1	1	
1040090044	90	63,0	60,0	33,0	84,0	78,0	17,5	0,224	1	1	
1040090045	90	75,0	60,0	33,0	100,0	81,5	18,5	0,273	1	1	
1040110046	110	63,0	73,5	37,0	84,0	86,0	21,5	0,356	1	1	
1040110047	110	75,0	73,5	37,0	100,0	89,0	22,0	0,383	1	1	
1040110048	110	90,0	73,5	37,0	120,0	99,0	29,0	0,500	1	1	
1040125049	125	75,0	84,0	40,0	100,0	101,0	31,0	0,518	1	1	
1040125050	125	90,0	84,0	40,0	120,0	99,0	26,0	0,588	1	1	
1040125051	125	110,0	84,0	40,0	147,0	112,0	35,0	0,832	1	1	



Reducing piece___





	D d	
7	n1	




RedSocke SDR 6 / 7,4 / 9 / 1		le / ins	side		Material: Standards: Colour:		fusiolen® F DIN 16962, DIN EN ISO 15 gi				
Article no.	d	d1	l	D	D1	L	Z	kg	PU	RG	
double sided socket	welding										
1040040073	40	32,0	20,5	52,0	43,0	44,0	5,5	0,035	1	1	
1040050074	50	32,0	23,5	68,0	43,0	53,0	11,5	0,066	1	1	
1040050075	50	40,0	23,5	68,0	52,0	50,5	6,3	0,069	1	1	
1040063076	63	40,0	27,5	84,0	52,0	61,0	13,0	0,115	1	1	
1040063077	63	50,0	27,5	84,0	68,0	56,0	5,0	0,120	1	1	
1040075078	75	50,0	30,0	100,0	68,0	68,0	14,5	0,192	1	1	
1040075079	75	63,0	30,0	100,0	84,0	62,5	5,0	0,185	1	1	
1040090080	90	63,0	33,0	120,0	84,0	74,0	13,5	0,276	1	1	
1040090081	90	75,0	33,0	120,0	100,0	69,0	6,0	0,297	1	1	
1040110082	110	75,0	37,0	147,0	100,0	85,0	18,0	0,516	1	1	
1040110083	110	90,0	37,0	147,0	120,0	77,3	7,3	0,520	1	1	
1040125084	125	90,0	40,0	167,0	120,0	91,0	18,0	0,749	1	1	
1040125085	125	110.0	40.0	167.0	147.0	87.0	10.0	0.726	1	1	


Reducing pie butt welding		t- and				erial: ndards: our:	DIN 169	fusiolen® PP-RC1 62, DIN EN ISO 15874 greer
Article no.	d	D	D1	L	Z	kg	PU	RG
one side socket weldin	ng, other side butt	welding						
SDR 9								
1043160122	110	147,0	160	90,0	53,0	0,694	1	1
1043160123	125	167,0	160	90,0	50,0	0,868	1	1
1043200124	125	167,0	200	135,0	95,0	1,599	1	1
SDR 11								
1044160053	110	147,0	160	90,0	53,0	0,673	1	1
1044160055	125	167,0	160	90,0	50,0	0,709	1	1
1044200057	125	167.0	200	135.0	95.0	1.341	1	1


Transition piece__

Reducing piece bu	tt welding			Material: Standards: Colour:	DIN 16	fusiolen® PP-R 962, DIN EN ISO 158 gre
Article no.	D	D1	L	kg	PU	RG
double sided butt welding						
SDR 9						
1043200125	200,0	160	135,0	1,588	1	1
1043250126	250,0	160	172,5	2,900	1	1
1043250127	250,0	200	172,5	3,206	1	1
1043315128	315,0	250	225,0	7,050	1	1
1043315131	315,0	200	225,0	6,350	1	1
SDR 11						
1044200059	200,0	160	135,0	1,140	1	1
1044250061	250,0	160	172,5	2,152	1	1
1044250063	250,0	200	172,5	2,681	1	1
1044315065	315,0	250	225,0	4,690	1	1



Transition with spanner flat	•			· till Cu	u		Standar Colour:	ds:	DIN	l 16962,	DIN E
Article no.	d	l	D	L	Z	z1	R	SW	kg	PU	RG
one side socket we	lding										
1070016007	16	34,5	38,5	50,5	37,5	10,0	1/2"	24	0,089	10	1
1070020008	20	34,5	38,5	50,5	36,0	10,0	1/2"	24	0,078	10	1
1070020009	20	29,0	43,5	50,0	35,5	10,0	3/4"	31	0,112	10	1
1070025010	25	36,0	38,5	52,0	36,0	10,0	1/2"	24	0,081	10	1
1070025011	25	29,0	43,5	50,0	34,0	10,0	3/4"	31	0,109	10	1
1070032012	32	32,0	43,5	53,0	35,0	10,0	3/4"	31	0,114	5	1
1070032013	32	37,5	60,0	59,5	41,5	14,0	1"	39	0,239	5	1
1070040014	40	40,0	60,0	62,0	41,5	14,0	1"	39	0,227	5	1
1070040015	40	40,0	74,0	63,0	42,5	15,0	1 1/4"	50	0,385	5	1
1070050016	50	43,0	74,0	66,0	42,5	15,0	1 1/4"	50	0,404	5	1
070050017	50	45,0	85,5	67,0	43,5	15,0	1 1/2"	55	0,418	5	1
1070063018	63	51,5	84,0	73,5	46,0	15,0	1 1/2"	55	0,442	1	1
1070063019	63	51,0	101,0	77,0	49,5	19,0	2"	67	0,600	1	1
1070075020	75	51,0	100,0	77,0	47,0	19,0	2"	67	0,608	1	1
1070032066 *	32	37,5	60,0	59,5	41,5	14,0	1"	39	0,232	5	1
1070040067 *	40	40,0	60,0	62,0	41,5	14,0	1"	39	0,219	5	1
1070040068 *	40	40,0	74,0	63,0	42,5	15,0	1 1/4"	50	0,331	5	1
070050069 *	50	43,0	74,0	66,0	42,5	15,0	1 1/4"	50	0,351	5	1
1070050070 *	50	45,0	84,0	67,0	43,5	15,0	1 1/2"	55	0,445	5	1
1070063071 *	63	51,5	84,0	73,5	46,0	15,0	1 1/2"	55	0,425	1	1
1070063072 *	63	51,0	101,0	77,0	49,5	19,0	2"	67	0,196	1	1
1070075073 *	75	51,0	100,0	77,0	47,0	19,0	2"	67	0,676	1	1






Transition piece__

Transition pround, self-sealin				Material: Standards Colour:	fusiolen® PP-R / DIN 16962, DIN EN ISO					
Article no.	d	D	L	Z	z2	R	kg	PU	RG	
one side socket weld	ding									
1070020051	20	38,5	52,5	38,0	12,0	1/2"	0,090	10	1	
1070025052	25	38,5	54,0	38,0	12,0	1/2"	0,078	10	1	
1070025053	25	38.5	53.5	37.5	13.0	3/4"	0.085	10	1	

Transition pi			Materia Standa Colour:	rds:	fusiolen® PP-R / brass or stain DIN 16962, DIN EN I				
Article no.	d	D	L	Z	z2	R	kg	PU	RG
one side socket weldin	9								
1070020022	20	38,5	56,5	42,0	16,0	1/2"	0,084	10	1
1070020023	20	38,5	57,5	43,0	17,0	3/4"	0,109	10	1
1070025024	25	38,5	58,0	42,0	16,0	1/2"	0,085	10	1
1070025025	25	38,5	57,5	41,5	17,0	3/4"	0,090	10	1
1070032026	32	38,5	59,5	41,5	17,0	3/4"	0,095	5	1
1070020074 *	20	38,5	56,5	42,0	16,0	1/2"	0,096	10	1
1070020075 *	20	38,5	57,5	43,0	17,0	3/4"	0,108	10	1
1070025076 *	25	38,5	58,0	42,0	16,0	1/2"	0,098	10	1
1070025077 *	25	38,5	57,5	41,5	17,0	3/4"	0,108	10	1
1070032078 *	32	38,5	59,5	41,5	17,0	3/4"	0,115	5	1
*stainless steel									





Transition p					Material: Standards: Colour:			fusiolen® PP-R / bras DIN 16962, DIN EN ISO 1587 gree			
Article no.	d	D	L	Z	z2	R	SW	kg	PU	RG	
one side socket weld	ing										
1070020056	20	38,5	63,5	49,0	13,0	1/2"	22	0,111	10	1	


Transition piece__

Transition pion with spanner flat, br						Standa Colour:		DII	l 16962,	DIN E
Article no.	d	D	L	Z	z2	R	SW	kg	PU	RG
one side socket weldin	g									
1070016026	16	38,5	66,5	53,5	16,0	1/2"	22	0,119	10	1
1070020027	20	38,5	66,5	52,0	16,0	1/2"	22	0,104	10	1
1070020028	20	38,5	67,5	53,0	17,0	3/4"	24	0,129	10	1
1070025029	25	38,5	68,0	52,0	16,0	1/2"	21	0,107	10	1
1070025030	25	38,5	67,5	51,5	17,0	3/4"	24	0,103	10	1
1070032031	32	53,0	78,5	60,5	20,0	1"	32	0,216	5	1
1070032032	32	68,0	81,0	63,0	21,0	1 1/4"	42	0,318	5	1
1070040033	40	52,0	81,0	60,5	20,0	1"	32	0,222	5	1
1070040034	40	68,0	84,5	64,0	21,0	1 1/4"	42	0,324	5	1
1070050035	50	68,0	85,5	62,0	21,0	1 1/4"	42	0,351	5	1
1070050036	50	74,0	88,5	65,0	22,0	1 1/2"	46	0,425	5	1
1070063037	63	72,5	94,5	67,0	22,0	1 1/2"	46	0,467	1	1
1070063038	63	84,0	102,5	75,0	23,5	2"	50	0,685	1	1
1070075039	75	84,0	102,0	72,0	23,5	2"	50	0,733	1	1
1070075040	75	100,0	105,0	75,0	26,7	2 1/2"	65	0,970	1	1
1070090041	90	120,0	121,0	88,0	30,0	3"	85	1,326	1	1
1070110042	110	147,0	148,0	111,0	39,0	4"	105	2,730	1	1
1070032079 *	32	53,0	78,5	60,5	20,0	1"	32	0,204	5	1
1070032080 *	32	68,0	81,0	63,0	21,0	1 1/4"	41	0,360	5	1
1070040081 *	40	52,0	81,0	60,5	20,0	1"	32	0,251	5	1
1070040082 *	40	68,0	84,5	64,0	21,0	1 1/4"	41	0,362	5	1
1070050083 *	50	68,0	85,5	62,0	21,0	1 1/4"	41	0,389	5	1
1070050084 *	50	74,0	88,5	65,0	22,0	1 1/2"	46	0,480	5	1
1070063085 *	63	72,5	94,5	67,0	22,0	1 1/2"	46	0,523	1	1
1070063086 *	63	84,0	102,5	75,0	23,5	2"	50	0,708	1	1
1070075087 * *stainless steel	75	84,0	102,0	72,0	23,5	2"	50	0,699	1	1

Transition p self-sealing., with — SDR 6 / 7,4 / 11	hexagon th				Material: Standards: Colour:			fusiolen® PP-R / DIN 16962, DIN EN ISO			
Article no.	d	D	L	Z	z2	R	SW	kg	PU	RG	
one side socket weld	ing										
1070020054	20	38,5	59,0	48,0	13,0	1/2"	22	0,107	10	1	









back to content

 back to content
 back to content

 back to content

 back to content

 back to content

 back to content

 back to content

 back to content

 back to content

 back to content

 back to content

 back to content

 back to content

 back to content
 back to content

 back to content

 back to content

 back to content

 back to content

 back to content

 back to content

 back to content

 back to content

 back to content

 back to content

 back to content

 back to content

 back to content

 back to content

 back to content

 content
 back to content

 back to content

 back to content

 content
 back to content

 content
 back to content

 content
 back to content


 content

 content
 content


 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 content
 c

96 Article list 97


Transition piece__



Transition-l brass or stainless					ad		St	aterial: andards: olour:	fusiolen® PP-R / brass or stainl DIN 16962, DIN EN IS		
Article no.	d	l	l1	D	D1	Z	z1	R	kg	PU	RG
one side socket weld	ling										
1070020091	20	37,0	37,0	34,0	44,0	22,5	24,0	3/4"	0,102	10	1
1070020092	20	31,0	31,5	29,5	37,0	16,5	18,5	1/2"	0,076	10	1
1070025093	25	37,0	37,0	34,0	44,0	21,0	24,0	3/4"	0,100	10	1
1070025094	25	33,5	31,5	34,0	37,0	17,5	18,5	1/2"	0,075	10	1
1070032095	32	27,5	51,0	43,0	44,0	9,5	38,0	3/4"	0,104	5	1
1070032096	32	34,0	66,5	43,0	60,5	16,0	44,5	1"	0,249	5	1
1070020110 *	20	37,0	37,0	29,5	37,0	22,5	24,0	3/4"	0,095	10	1
1070020111 *	20	31,0	31,5	29,5	37,0	16,5	18,5	1/2"	0,081	10	1
1070025112 *	25	37,0	37,0	34,0	44,0	21,0	24,0	3/4"	0,101	10	1
1070025113 *	25	33,5	31,5	34,0	37,0	17,5	18,5	1/2"	0,082	10	1
1070032114 *	32	35,0	37,0	43,0	37,0	17,0	24,0	1/2"	0,112	5	1
1070032115 *	32	27,5	51,0	43,0	44,0	9,5	38,0	3/4"	0,097	5	1
1070032116 *	32	34,0	66,5	43,0	60,5	16,0	44,5	1"	0,240	5	1
*stainless steel											




Transition SDR 6 / 7,4 / 1		w wit	h fem	ale th	read			Material: Standards: Colour:		fusio DIN 16962	len® PP , DIN EN	
Article no.	d	l	l1	D	D1	Z	z 1	R	kg	PU	RG	
one side socket w	elding/											
1070020097	20	33,5	37,0	29,5	37,0	18,5	24,0	1/2"	0,076	10	1	




Transition- brass or stainless				read			Material: Standard Colour:		len® PP-R / DIN '		or stainle DIN EN IS
Article no.	d	l	l1	D	D1	Z	z2	R	kg	PU	RG
one side socket wel	ding										
1070020099	20	31,5	53,0	29,5	37,0	17,0	16,0	1/2"	0,108	10	1
1070020100	20	31,5	54,0	34,0	38,0	17,0	17,0	3/4"	0,128	10	1
1070025101	25	31,5	54,0	34,0	38,0	15,5	17,0	3/4"	0,104	10	1
1070032102	32	27,5	68,0	43,0	38,0	9,5	17,0	3/4"	0,112	5	1
1070032103	32	31,0	85,5	43,0	52,0	13,0	20,0	1"	0,231	5	1
1070020117 *	20	31,5	53,0	29,5	37,0	17,0	16,0	1/2"	0,035	10	1
1070020118 *	20	31,5	54,0	34,0	38,0	17,0	17,0	3/4"	0,123	10	1
1070025119 *	25	31,5	54,0	34,0	38,0	15,5	17,0	3/4"	0,121	10	1
1070032120 *	32	27,5	68,0	43,0	38,0	9,5	17,0	3/4"	0,128	5	1
*stainless steel											

Transition piece__


Transition- brass or stainless				ie ilire	du		Mater Stand Colou	ards:	olen® PP-R DIN		DIN EN ISC	
Article no.	d	l	l1	D	D1	Z	z1	R	kg	PU	RG	
double sided socket	welding											
1060020141	20	31,5	37,0	29,5	37,0	17,0	24,0	1/2"	0,086	10	1	
1060020142	20	37,0	37,0	34,0	44,0	22,5	24,0	3/4"	0,121	10	1	
1060025143	25	34,0	38,0	34,0	37,0	18,0	25,0	1/2"	0,090	10	1	
1060025144	25	37,0	37,0	34,0	44,0	21,0	24,0	3/4"	0,109	10	1	
1060032145	32	35,0	37,0	43,0	37,0	17,0	24,0	1/2"	0,103	5	1	
1060032146	32	27,5	51,0	43,0	44,0	9,5	38,0	3/4"	0,111	5	1	
1060032147	32	31,5	67,0	43,0	60,0	13,5	45,0	1"	0,255	5	1	
1060040148	40	42,0	40,0	52,0	37,0	21,5	27,0	1/2"	0,142	5	1	
1060040149	40	40,5	40,5	52,0	52,0	20,0	27,5	3/4"	0,147	5	1	
1060040150	40	41,5	56,0	52,0	60,0	21,0	34,0	1"	0,276	5	1	
1060050151	50	49,5	63,5	68,0	60,0	26,0	41,5	1"	0,385	5	1	
1060050152	50	49,5	44,5	68,0	43,0	26,0	31,5	1/2"	0,237	5	1	
1060050153	50	49,5	44,5	68,0	43,0	26,0	31,5	3/4"	0,243	5	1	
1060020160 *	20	31,5	37,0	29,5	37,0	17,0	24,0	1/2"	0,087	10	1	
1060020161 *	20	37,0	37,0	34,0	44,0	22,5	24,0	3/4"	0,108	10	1	
1060025162 *	25	34,5	38,0	34,0	37,0	18,5	25,0	1/2"	0,093	10	1	
1060025163 *	25	37,0	37,0	34,0	44,0	21,0	24,0	3/4"	0,111	10	1	
1060032164 *	32	35,0	37,0	43,0	37,0	17,0	24,0	1/2"	0,113	5	1	
1060032165 *	32	27,5	51,0	43,0	44,0	9,5	38,0	3/4"	0,111	5	1	
1060032166 *	32	31,5	67,0	43,0	60,0	13,5	45,0	1"	0,082	5	1	
*stainless steel												



Transition p						Materia Standa Colour:	rds:		iss or stainles 52, DIN EN ISO
Article no.	d	l	D	L	Z	R	kg	PU	RG
one side socket weldi	ng								
1070020002	20	27,5	37,5	40,5	26,0	1/2"	0,064	10	1
1070020003	20	27,5	43,5	40,5	26,0	3/4"	0,089	10	1
1070025004	25	29,5	38,5	42,5	26,5	1/2"	0,065	10	1
1070025005	25	27,5	43,5	40,5	24,5	3/4"	0,087	10	1
1070032006	32	30,5	43,5	43,5	25,5	3/4"	0,092	5	1
1070020060 *	20	27,5	37,5	40,5	26,0	1/2"	0,069	10	1
1070020061 *	20	27,5	43,5	40,5	26,0	3/4"	0,090	10	1
1070025062 *	25	29,5	38,5	42,5	26,5	1/2"	0,069	10	1
1070025063 *	25	27,5	43,5	40,5	24,5	3/4"	0,086	10	1
1070032064 *	32	30,5	43,5	43,5	25,5	3/4"	0,092	5	1
1070032065 * *stainless steel	32	28,0	37,0	41,0	23,0	1/2"	0,078	5	1



Weld-in and weld-on saddle ___




Weld-in sad SDR 6 / 7,4 / 9 / 1						Material Standari Colour:		DIN 1696	fusiolen® PP-R 2, DIN EN ISO 15874 green
Article no.	D1	d	d2	l	D	z2	kg	PU	RG
socket welding									
1030040001 *	40	20	25,0	27,0	29,5	14,5	0,016	5	1
1030040002 *	40	25	25,0	28,5	34,0	16,0	0,017	5	1
1030050003	50	20	25,0	27,5	29,5	14,5	0,018	5	1
1030050004	50	25	25,0	28,5	34,0	16,0	0,019	5	1
1030063005	63	20	25,0	27,5	29,5	14,5	0,017	5	1
1030063006	63	25	25,0	28,5	34,0	16,0	0,019	5	1
1030063007	63	32	32,0	30,0	43,0	18,0	0,028	5	1
1030075008	75	20	25,0	27,5	29,5	14,5	0,018	5	1
1030075009	75	25	25,0	28,5	34,0	16,0	0,019	5	1
1030075010	75	32	32,0	30,0	43,0	18,0	0,028	5	1
1030075011	75	40	40,0	34,0	52,0	20,5	0,049	5	1
1030090012	90	20	25,0	27,5	29,5	14,5	0,018	5	1
1030090013	90	25	25,0	28,5	34,0	16,0	0,019	5	1
1030090014	90	32	32,0	30,0	43,0	18,0	0,029	5	1
1030090015	90	40	40,0	34,0	52,0	20,5	0,048	5	1
1030110016	110	20	25,0	27,5	29,5	14,5	0,019	5	1
1030110017	110	25	25,0	28,5	34,0	16,0	0,020	5	1
1030110018	110	32	32,0	30,0	43,0	18,0	0,030	5	1
1030110019	110	40	40,0	34,0	52,0	20,5	0,050	5	1
1030110020	110	50	50,0	34,0	68,0	23,5	0,091	5	1
1030125021	125	20	25,0	27,5	29,5	14,5	0,019	5	1
1030125022	125	25	25,0	28,5	34,0	16,0	0,020	5	1
1030125023	125	32	32,0	30,0	43,0	18,0	0,029	5	1
1030125024	125	40	40,0	34,0	52,0	20,5	0,050	5	1
1030125025	125	50	50,0	34,0	68,0	23,5	0,090	5	1
1030125026	125	63	63,0	38,0	84,0	27,5	0,149	5	1
1030160027	160	20	25,0	27,5	29,5	14,5	0,021	5	1
1030160028	160	25	25,0	28,5	34,0	16,0	0,023	5	1
1030160029	160	32	32,0	30,0	43,0	18,0	0,034	5	1
1030160030	160	40	40,0	34,0	52,0	20,5	0,054	5	1
1030160031	160	50	50,0	34,0	68,0	23,5	0,094	5	1
1030160032	160	63	63,0	38,0	84,0	27,5	0,157	5	1
1030160033	160	75	75,0	42,0	100,0	30,0	0,238	5	1
1030160034	160	90	90,0	45,0	120,0	33,0	0,360	5	1
1030250035	200-250	20	25,0	27,5	29,5	14,5	0,020	5	1
1030250036	200-250	25	25,0	28,5	34,0	16,0	0,021	5	1
1030250037	200-250	32	32,0	30,0	43,0	18,0	0,031	5	1
1030200038	200	40	40,0	34,0	52,0	20,5	0,049	5	1
1030200039	200	50	50,0	34,0	68,0	23,5	0,087	5	1
1030200040	200	63	63,0	37,5	84,0	27,5	0,146	5	1
1030200041	200	75	75,0	42,0	100,0	30,0	0,225	5	1
1030200042	200	90	90,0	45,0	120,0	33,0	0,356	5	1
1030200043	200	110	110,0	49,0	147,0	37,0	0,638	5	1
1030200044	200	125	125,0	55,0	167,0	40,0	0,862	5	1

*not for aquatherm blue pipe OT continued on next page ...

Weld-in and weld-on saddle ___


Weld-in sa (Continued) SDR	addle 6/7,4/9/11.	/ 17,6				Materia Standar Colour:		DIN 1696	en® PP- SO 1587 gree	
Article no.	D1	d	d2	l	D	z2	kg	PU	RG	
1030250045	250	40	40,0	34,0	52,0	20,5	0,053	5	1	
1030250046	250	50	50,0	34,0	68,0	23,5	0,090	5	1	
1030250047	250	63	63,0	37,5	84,0	27,5	0,152	5	1	
1030250048	250	75	75,0	42,0	100,0	30,0	0,222	5	1	
1030250049	250	90	90,0	45,0	120,0	33,0	0,348	5	1	
1030250050	250	110	110,0	49,0	147,0	37,0	0,602	5	1	
1030250051	250	125	125,0	55,0	167,0	40,0	0,820	5	1	
1030315052	315-355	63	63,0	37,5	84,0	27,5	0,153	1	1	
1030315053	315-355	75	75,0	42,0	100,0	30,0	0,230	1	1	
1030315054	315	90	90,0	45,0	120,0	33,0	0,363	1	1	
1030315055	315	110	110,0	49,0	147,0	37,0	0,592	1	1	
1030315056	315	125	125,0	55,0	167,0	40,0	0,830	1	1	



With weld-on surface and additional weld-in socket for fusion with the pipe wall. The tools required for processing are listed from page /.


Weld-in saddle	e butt-weld		Material: Standards: Colour:		fusiolen® PP-RCT / DIN 16962, DIN EN				
Article no.	D1	D	d2	l	L	kg	PU	RG	
butt welding									
SDR 9									
1033315073	315	160,0	160,0	80,0	237,5	0,831	1	1	
1033355074	355	160,0	160,0	80,0	257,5	0,845	1	1	
SDR 11									
1034315057	315	160,0	160,0	80,0	237,5	0,862	1	1	
1034355061	355	160,0	160,0	80,0	257,5	0,867	1	1	

With weld-on surface and additional weld-in socket for fusion with the pipe wall. The tools required for processing are listed from page 178.



100 Article list Article list 101

Weld-in and weld-on saddle ___



Weld-in sa With spanner fla				ad		Mater Stand Colou	ards:	DI	fusiolen® PP-I DIN 16962, DIN EN IS		
Article no.	D1	d	l	D	z2	R	SW	kg	PU	RG	
socket welding											
1030040100 *	40	25	39,0	38,5	16,0	1/2"	24	0,088	5	1	
1030050106	50	25	39,0	38,5	16,0	1/2"	24	0,090	5	1	
1030063112	63	25	39,0	38,5	16,0	1/2"	24	0,089	5	1	
1030075118	75	25	39,0	38,5	16,0	1/2"	24	0,083	5	1	
1030090126	90	25	39,0	38,5	16,0	1/2"	24	0,090	5	1	
1030110134	110	25	39,0	38,5	16,0	1/2"	24	0,089	5	1	
1030125142	125	25	39,0	38,0	16,0	1/2"	24	0,092	5	1	
1030160150	160	25	39,0	38,5	16,0	1/2"	24	0,092	5	1	
1030250158	200-250	25	39,0	38,5	16,0	1/2"	24	0,092	5	1	
1030040101	40	25	39,0	43,5	21,0	3/4"	31	0,107	5	1	
1030050107	50	25	39,0	43,5	21,0	3/4"	31	0,110	5	1	
1030063113	63	25	39,0	43,5	21,0	3/4"	31	0,109	5	1	
1030075119	75	25	39,0	43,5	21,0	3/4"	31	0,109	5	1	
1030090127	90	25	39,0	43,5	21,0	3/4"	31	0,110	5	1	
1030110135	110	25	39,0	43,5	21,0	3/4"	31	0,110	5	1	
1030125143	125	25	39,0	43,5	21,0	3/4"	31	0,112	5	1	
1030160151	160	25	39,0	43,5	21,0	3/4"	31	0,112	5	1	
1030250159	200-250	25	39,0	43,5	21,0	3/4"	31	0,112	5	1	
1030075120	75	32	43,0	60,0	22,0	1"	39	0,223	5	1	
1030090128	90	32	43,0	60,0	22,0	1"	39	0,223	5	1	
1030110136	110	32	43,0	60,0	22,0	1"	39	0,223	5	1	
1030125144	125	32	43,0	60,0	22,0	1"	39	0,224	5	1	
1030160152	160	32	43,0	60,0	22,0	1"	39	0,226	5	1	
1030250160	200-250	32	43,0	60,0	22,0	1"	39	0,244	5	1	

D SW
77

*not for aquatherm blue pipe OT

With weld-on surface and additional weld-in socket for fusion with the pipe wall. The tools required for processing are listed from page 178.


Weld-in sadd With spanner flat —						Materi Standa Colour	ards:	DIN		en® PP-R / bi DIN EN ISO 15 gr
Article no.	D1	d	l	D	z2	R	SW	kg	PU	RG
one side socket welding	ı									
1030040102 *	40	25	55,0	38,5	16,0	1/2"	21	0,088	5	1
1030050108	50	25	55,0	38,5	16,0	1/2"	21	0,090	5	1
1030063114	63	25	55,0	38,5	16,0	1/2"	21	0,089	5	1
1030075121	75	25	55,0	38,5	16,0	1/2"	21	0,097	5	1
1030090129	90	25	55,0	38,5	16,0	1/2"	21	0,090	5	1
1030110137	110	25	55,0	38,5	16,0	1/2"	21	0,089	5	1
1030125145	125	25	55,0	38,5	16,0	1/2"	21	0,092	5	1
1030160153	160	25	55,0	38,5	16,0	1/2"	21	0,092	5	1
1030040103 *	40	25	56,0	43,5	17,0	3/4"	24	0,107	5	1
1030050109	50	25	56,0	43,5	17,0	3/4"	24	0,110	5	1
1030063115	63	25	56,0	43,5	17,0	3/4"	24	0,109	5	1
1030075122	75	25	56,0	43,5	17,0	3/4"	24	0,109	5	1
1030090130	90	25	56,0	43,5	17,0	3/4"	24	0,110	5	1
1030110138	110	25	56,0	43,5	17,0	3/4"	24	0,110	5	1
1030125146	125	25	56,0	43,5	17,0	3/4"	24	0,112	5	1
1030160154	160	25	56,0	43,5	17,0	3/4"	24	0,112	5	1
*not for aquatherm blue	e pipe OT									


Weld-in and weld-on saddle ___

Weld-in sa (SDR 6 / 7,4 / 9 / 7		femal		Materia Standa Colour:	rds:		R / stainl DIN EN I				
Article no.	D1	d	l	D	z2	R	SW	kg	PU	RG	
one side socket wel	ding										
1030040104 **	40	25	39,0	38,5	16,0	1/2"	-	0,062	5	1	
1030050110	50	25	39,0	38,5	16,0	1/2"	-	0,064	5	1	
1030063116	63	25	39,0	38,5	16,0	1/2"	-	0,064	5	1	
1030075123	75	25	39,0	38,5	16,0	1/2"	-	0,064	5	1	
1030090131	90	25	39,0	38,5	16,0	1/2"	-	0,064	5	1	
1030110139	110	25	39,0	38,5	16,0	1/2"	-	0,069	5	1	
1030125147	125	25	39,0	38,5	16,0	1/2"	-	0,065	5	1	
1030160155	160	25	39,0	38,5	16,0	1/2"	-	0,066	5	1	
1030250161	200-250	25	39,0	38,5	16,0	1/2"	-	0,065	5	1	
1030040105	40	25	39,0	43,5	21,0	3/4"	-	0,082	5	1	
1030050111	50	25	39,0	43,5	21,0	3/4"	-	0,074	5	1	
1030063117	63	25	39,0	43,5	21,0	3/4"	-	0,073	5	1	
1030075124	75	25	39,0	43,5	21,0	3/4"	-	0,074	5	1	
1030090132	90	25	39,0	43,5	21,0	3/4"	-	0,074	5	1	
1030110140	110	25	39,0	43,5	21,0	3/4"	-	0,083	5	1	
1030125148	125	25	39,0	43,5	21,0	3/4"	-	0,074	5	1	
1030160156	160	25	39,0	43,5	21,0	3/4"	-	0,076	5	1	
1030250162	200-250	25	39,0	43,5	21,0	3/4"	-	0,084	5	1	
1030075125 *	75	32	43,0	60,0	22,0	1"	39	0,234	5	1	
1030090133 *	90	32	43,0	60,0	22,0	1"	39	0,235	5	1	
1030110141 *	110	32	43,0	60,0	22,0	1"	39	0,236	5	1	
1030125149 *	125	32	43,0	60,0	22,0	1"	39	0,235	5	1	
1030160157 *	160	32	43,0	60,0	22,0	1"	39	0,238	5	1	
1030250163 *	200-250	32	43,0	60,0	22,0	1"	39	0,237	5	1	



aquatherm weld-on with ball valve for mounting und in use with hot tapping tool — St	er pressure	7.6	Material: Standards: Colour:	fusiole DIN 16962, DIN EN IS
Article no.	d	D1	PU	RG
socket welding				
1090075010	40	75	1	1
1090090011	40	90	1	1
1090110012	40	110	1	1
1090125013	40	125	1	1
1090125014	63	125	1	1
1090160015	40	160	1	1
1090160016	63	160	1	1
1090200017	40	200	1	1
1090200018	63	200	1	1
1090250019	40	250	1	1
1090250020	63	250	1	1
1090315021	63	315-355	1	1
1090400022	63	400-630	1	1







^{*}with hexagon threaded transition
***not for aquatherm blue pipe OT


fusiolen® PP-R

DIN 16962, DIN EN ISO 15874


Screwed connections___

D d

Water met with gasket — S		•	Mai Sta Col	DII	fusiolen® PP-R DIN 16962, DIN EN IS						
Article no.	d	l	l1	D	Z	R	SW	kg	PU	RG	
one side socket w	elding										
1050020090	20	59,5	3,0	38,5	45,0	3/4"	30	0,136	1	1	
1050025091	25	61,0	3,0	38,5	45,0	3/4"	30	0,155	1	1	
1050032092	32	62.0	3.0	43.5	44.0	3/4"	30	0.162	1	1	



Coupling s SDR 6 / 7,4 / 9 /	•	oint, bra	SS		Material: Standards: Colour:	Di	fusiolen® PP-R / bras DIN 16962, DIN EN ISO 1587 green, bras			
Article no.	d	l	D	Z	SW1	SW2	kg	PU	RG	
socket welding										
1050032040	32	36,5	41,0	18,5	64	50	0,479	1	1	
1050040041	40	38,0	50,0	17,5	80	60	0,841	1	1	
1050050042	50	41,0	61,0	17,5	86	70	0,821	1	1	
1050063043	63	45,0	76,0	17,5	108	90	1,498	1	1	
1050075044	75	31,0	90,0	17,5	128	104	1,998	1	1	




Coupling screw joint SDR 6/7,4/9/11


Article no.	d	l	l1	D	Z	z1	kg	PU	RG
socket welding									
1050020050	20	26,0	20,0	46,0	12,0	5,5	0,036	10	1
1050025051	25	28,0	21,0	56,0	12,0	5,0	0,058	10	1
1050032052	32	30,0	23,0	66,0	12,0	5,0	0,089	5	1
1050040053	40	34,0	25,5	79,0	13,5	5,0	0,136	5	1
1050050054	50	39,0	28,8	87,0	15,5	5,0	0,170	5	1
1050063055	63	47,5	32,5	107,0	20,0	5,0	0,240	1	1
1050075056	75	50,0	36,0	128,0	20,0	6,0	0,546	1	1

Screwed connections ___


Loose nut adapter with gasket — SDR 6 / 7,4 / 9 / 11						Material: Standards: DI Colour:				R / bras SO 1587 gree
Article no.	d	l	l1	k	R	SW	kg	PU	RG	
one side socket wel	lding									
1050020082	20	100,0	3,0	65,0	1"	36	0,079	1	1	
1050025083	25	100,0	3,0	62,0	1 1/4"	46	0,104	1	1	
1050032084	32	100,0	3,0	58,0	1 1/2"	52	0,175	1	1	
1050040085	40	100 0	3 በ	53 N	2"	64	N 258	1	1	



Transition male three with union nut	ad	·		/7,4/9/		Materia Standa Colour	rds:	fusiolen® PP-R / bi DIN 16962, DIN EN ISO 15 gr				
Article no.	d	D	L	Z	z2	R	SW1	SW2	kg	PU	RG	
one side socket v	velding											
1050020070	20	27,5	52,5	38,0	13,5	1/2"	34	36	0,145	1	1	
1050025071	25	36,0	59,5	43,5	14,5	3/4"	42	46	0,243	1	1	
1050032072	32	41,5	64,5	46,5	16,8	1"	48	52	0,336	1	1	
1050040073	40	53,0	70,0	49,5	19,1	1 1/4"	60	64	0,517	1	1	
1050050074	50	59,0	84,8	61,3	22,0	1 1/2"	48	72	0,624	1	1	
1050063075	63	74,0	95,5	68,0	25,0	2"	62	89	1,045	1	1	



Transition female the with union nut a	read	•		7,4/9/1		Materia Standar Colour:	fusiolen® PP-R / bra DIN 16962, DIN EN ISO 158' gre					
Article no.	d	D	L	Z	z2	R	SW1	SW2	kg	PU	RG	
one side socket we	elding											
1050020076	20	27,5	45,0	30,5	15,0	1/2"	36	24	0,112	1	1	
1050025077	25	36,0	49,0	33,0	15,5	3/4"	46	32	0,193	1	1	
1050032078	32	41,5	54,0	36,0	15,0	1"	52	40	0,291	1	1	
1050040079	40	53,0	56,5	36,0	20,0	1 1/4"	64	47	0,423	1	1	
1050050080	50	59,0	64,8	41,3	19,0	1 1/2"	72	57	0,610	1	1	
1050063081	63	74.0	74.5	47,0	18.0	2"	89	68	0.924	1	1	



104 Article list Article list 105

Screwed connections___


Nut adapter SDR 6 / 7,4 / 9 / 1		Materi Standa Colour	DII	fusiolen® Pi DIN 16962, DIN EN						
Article no.	d	l	l1	D	Z	R	SW	kg	PU	RG
one side socket weld	ing									
1050020097	20	58,5	3,0	38,5	34,0	1"	36	0,182	10	1
1050025098	25	60,0	3,0	38,5	44,0	1"	36	0,186	10	1
1050025099	25	60,0	3,0	43,5	44,0	1 1/4"	46	0,274	10	1
1050032100	32	63,0	3,0	43,5	45,0	1 1/4"	46	0,279	5	1
1050032101	32	69,5	3,0	60,0	51,5	1 1/2"	52	0,446	5	1
1050040102	40	72,0	3,0	60,0	51,5	1 1/2"	52	0,421	5	1
1050040103	40	72,0	3,0	74,0	51,5	2"	64	0,719	5	1
1050050104	50	75,0	3,0	74,0	51,5	2"	64	0,736	5	1
1050050105	50	77,0	3,0	84,0	53,5	2 1/4"	72	0,831	5	1
1050063106	63	83,5	3,0	84,0	56,0	2 1/4"	72	0,889	1	1
1050063107	63	82,5	3,0	101,0	55,0	2 3/4"	89	1,306	1	1
1050075108	75	85,0	3,0	100,0	55,0	2 3/4"	89	1,275	1	1
1050075109	75	91,0	3,0	100,0	61,0	3 1/2"	110	1,818	1	1



	D -
L	
 	R



Counterpart with welding socket			Stan	Material: Standards: 1 Colour:			fusiolen® PP-F DIN 16962, DIN EN IS			
Article no.	d	D	L	Z	R	SW	kg	PU	RG	
one side socket weldin	g									
1050020110	20	37,5	61,5	47,0	1"	24	0,151	10	1	
1050025111	25	37,5	63,0	47,0	1"	24	0,153	10	1	
1050025112	25	43,5	63,0	47,0	1 1/4"	31	0,221	10	1	
1050032113	32	43,5	66,0	48,0	1 1/4"	31	0,226	5	1	
1050032114	32	60,0	76,5	58,5	1 1/2"	39	0,408	5	1	
1050040115	40	60,0	79,0	58,5	1 1/2"	39	0,414	5	1	
1050040116	40	74,0	79,0	58,5	2"	50	0,650	5	1	
1050050117	50	74,0	82,0	58,5	2"	50	0,634	5	1	
1050050118	50	84,0	83,0	59,5	2 1/4"	55	0,750	5	1	
1050063119	63	84,0	89,5	62,0	2 1/4"	55	0,728	1	1	
1050063120	63	101,0	95,0	65,5	2 3/4"	67	1,093	1	1	
1050075121	75	100,0	95,0	65,0	2 3/4"	67	1,117	1	1	
1050075122	75	100,0	100,0	70,0	3 1/2"	67	1,436	1	1	



brass counte to ISO-Norm-screwe	•			Mate	rial:				ı	
Article no.	l1	L	z2	R1	R2	SW	kg	PU	RG	
1050000130	14,0	25,0	15,0	1"	1/2"	25	0,063	10	1	
1050000131	12,5	26,0	14,0	1 1/4"	3/4"	32	0,119	10	1	
1050000132	15,0	31,0	17,0	1 1/2"	1"	40	0,175	5	1	
1050000133	17,0	33,0	22,0	2"	1 1/4"	47	0,263	5	1	
1050000134	20,0	36,0	19,0	2 1/4"	1 1/2"	57	0,333	5	1	
1050000135	24,0	42,0	24,0	2 3/4"	2"	68	0,517	1	1	
9600027522	24,0	46,0	27,0	3 1/2"	2 1/2"	84	0,801	1	1	
9600027524	27,0	46,0	27,0	4"	3"	97	0,943	1	1	

Flange adapter ___


	erpart with male thread d connection — SDR 6 / 7.4 / 9 / 11											
Article no.	l1	L	z2	R1	R2	SW	kg	PU	RO			
1050000138	17,5	32,5	10,5	1"	1/2"	34	0,109	10	1			
1050000139	21,0	38,5	12,5	1 1/4"	3/4"	42	0,188	10	1			
1050000140	22,5	41,5	13,5	1 1/2"	1"	48	0,211	5	1			
1050000141	22,5	44,5	13,0	2"	1 1/4"	60	0,363	5	1			
1050000142	34,0	56,0	16,0	2 1/4"	1 1/2"	48	0,472	5	1			
1050000143	38,0	63,0	16,0	2 3/4"	2"	62	0,803	1	1			
9600027722	42,0	70,0	22,0	3 1/2"	2 1/2"	82	1,189	1	1			
9600027724	42,0	74,0	22,0	4"	3"	97	1,398	1	1			


Flange adap SDR 6 / 7,4 / 9 / 11	ter with	ı gaske		Material: Standards: Colour:			fusio Din 16962, din en				
Article no.	d	L	l	D	D1	z1	z2	kg	PU	RG	
one side socket weldin	g										
1050032020	32	34,0	10,0	41,0	68,0	16,0	3,0	0,053	1	1	
1050040021	40	35,5	11,0	50,0	78,0	15,0	3,0	0,071	1	1	
1050050022	50	39,5	12,0	61,0	88,0	16,0	3,0	0,071	1	1	
1050063023	63	43,5	14,0	76,0	102,0	16,0	3,0	0,112	1	1	
1050075024	75	46,0	16,0	90,0	122,0	16,0	3,0	0,169	1	1	
1050090025	90	50,0	17,0	108,0	138,0	17,0	3,0	0,261	1	1	
1050110026	110	55,5	18,5	131,0	158,0	18,5	3,0	0,329	1	1	
1050125028	125	63,0	20,0	165,0	188,0	23,0	3,0	0,724	1	1	
1050125027 *	125	195,0	18,5	131,0	158,0	-	3,0	1,180	1	1	




Flange adapton	er butt	weldir	ng			Materia Standa Colour:		DIN 16962,		
Article no.	d	l	D	D1	L	z2	kg	PU	RG	
one side butt welding										
SDR 9										
1023160000 *	160	25,0	175,0	212,0	93,0	3,0	1,150	1	1	
1023200031	200	32,0	232,0	268,0	130,0	6,0	2,292	1	1	
1023250032	250	35,0	285,0	320,0	130,0	6,0	3,313	1	1	
1023315033	315	52,0	337,0	370,0	172,5	6,0	5,640	1	1	
SDR 11										
1054160030	160	25,0	175,0	212,0	93,0	3,0	0,955	1	1	
1054200032	200	32,0	232,0	268,0	130,0	6,0	1,957	1	1	
1054250034	250	35,0	285,0	320,0	130,0	6,0	2,717	1	1	
1054315035	315	35,0	335,0	370,0	168,0	6,0	6,000	1	1	

^{*}Up to 160 mm EPDM seal without steel ring insert. From 200 mm EPDM seal with steel ring insert. Suitable flange adapter for shutt-off valve available on request.







SDR 6 / 7,4 / 9 / 11 / 17,

106 Article list Article list 107

Flange adapter ___

Flange adapt without gasket	er incl	. Flang	e PN6			Material: Standards: Colour:		Flange: steel galvanised, Flange adapter: fusiolen® PP-R Flange according to DIN 2641 Flange: black / Flange adapter: green			
Article no.	d	D	d1	l	l1	L	n	kg	PU	RG	
socket welding											
SDR 6 / 7,4 / 9 / 11 / 17	7,6										
1050032001	32	100,0	75,0	10,0	10,0	34,0	4	1,090	1	1	
1050040002	40	120,0	90,0	11,0	10,0	35,5	4	1,170	1	1	
1050050003	50	130,0	100,0	12,0	10,0	39,5	4	1,360	1	1	
1050063004	63	140,0	110,0	14,0	10,0	43,5	4	0,886	1	1	
1050075005	75	160,0	130,0	16,0	10,0	46,0	4	1,148	1	1	
1050090006	90	190,0	150,0	17,0	10,0	50,0	4	1,618	1	1	
1050110007	110	210,0	170,0	18,5	10,0	55,5	4	1,824	1	1	
1050125009	125	240,0	200,0	20,0	12,0	63,0	4	3,945	1	1	
SDR 6 / 7,4 / 9 / 11 / 17	1,6										
1050125008 *	125	210,0	170,0	18,5	10,0	195,0	8	2,715	1	1	
butt welding											
SDR 11											
1050160010	160	265,0	225,0	25,0	12,0	93,0	8	4,136	1	1	
1050200011	200	320,0	280,0	32,0	12,0	130,0	8	6,694	1	1	
1050250012	250	375,0	335,0	35,0	12,0	130,0	8	9,500	1	1	

d = Connection dimension, d1 = hole-circle, PN 6 = Flange according to DIN 2641

^{*125} mm Fitting with 110 mm, flange adapter incl. flange PN6 use only in combination with a fitting

Plastic coa SDR 6 / 7,4 / 9 / 1		lange		Material: PI Standards: Flange acct DIN EN 1092, D Colour:							2, DIN 2501		
Article no.	titting Art no	Flange Idapter	DN	d	d1	D	d2	L	n	kg	PU	RG	grey
1040032130	1050032020	32	25	42,0	85,0	116,0	14,0	15,5	4	0,469	1	1	
1040040131	1050040021	40	32	51,0	100,0	141,0	18,0	17,5	4	0,722	1	1	
1040050132	1050050022	50	40	62,0	110,0	151,0	18,0	17,5	4	0,770	1	1	
1040063133	1050063023	63	50	78,0	125,0	166,0	18,0	19,0	4	0,911	1	1	
1040075134	1050075024	75	65	92,0	145,0	186,0	18,0	19,0	4	1,132	1	1	
1040090135	1050090025	90	80	110,0	160,0	201,0	18,0	21,0	8	1,356	1	1	
1040110136	1050110026 1050125027	110	100	133,0	180,0	221,0	18,0	22,0	8	1,475	1	1	
1040125137	1050125028 (125 mm)	125	125	167,0	210,0	251,0	18,0	26,0	8	2,082	1	1	
1040160138	1052160029 1054160030	160	150	178,0	240,0	286,0	22,0	27,0	8	3,671	1	1	
1040200139	1052200031 1054200032	200	200	235,0	295,0	341,0	22,0	28,0	8	4,709	1	1	
1040250140	1052250033 1054250034	250	250	288,0	350,0	406,0	22,0	31,0	12	7,094	1	1	
1040315141	1054315035	315	300	340,0	400,0	460,0	22,0	33,5	12	9,500	1	1	
1040355142	1054355036	355	350	376,0	460,0	520,0	22,0	39,0	16	15,300	1	1	
1040400143	2057400105	400	400	430,0	515,0	565,0	26,0	34,0	16	19,680	1	1	
1040450144 *	2057450106	450	500	517,0	620,0	670,0	26,0	42,0	20	22,880	1	1	
1040500145 *	2057500107	500	500	533,0	620,0	670,0	26,0	38,0	20	19,000	1	1	
1040630146 *	2057630108	630	600	645,0	725,0	785,0	30,0	40,0	20	25,800	1	1	

Valves__

PP-ball valve, with union nut and welding socket SDR 6/7.4/9/11							Material: Colour:					fusiolen® PF gre		
d	d1	D	h	l1	12	13	L	l	kg	PU	RG			
20	13,5	50,3	48,0	25,0	56,5	68,0	97,0	48,0	0,118	1	1			
25	18,5	59,0	56,5	25,0	65,5	78,0	110,0	59,0	0,184	1	1			
32	23,9	70,3	64,5	26,0	72,0	84,5	120,5	59,0	0,274	1	1			
40	31,0	85,9	83,3	45,0	85,0	100,0	141,0	63,5	0,483	1	1			
50	38,5	99,5	89,4	45,0	89,0	107,0	154,0	63,5	0,648	1	1			
63	50,0	125,5	115,0	45.0	101.0	118.0	173.0	108.0	1.206	1	1			
	cket / 11 d 20 25 32 40 50	d d1 20 13.5 25 18.5 32 23.9 40 31.0 50 38.5	d d1 D 20 13.5 50.3 25 18.5 59.0 32 23.9 70.3 40 31.0 85.9 50 38.5 99.5	ocket d d1 D h 20 13.5 50.3 48.0 25 18.5 59.0 56.5 32 23.9 70.3 64.5 40 31.0 85.9 83.3 50 38.5 99.5 89.4	ocket / 11 d d1 D h l1 20 13,5 50,3 48,0 25,0 25 18,5 59,0 56,5 25,0 32 23,9 70,3 64,5 26,0 40 31,0 85,9 83,3 45,0 50 38,5 99,5 89,4 45,0	Ocket d d1 D l1 l2 20 13,5 50,3 48,0 25,0 56,5 25 18,5 59,0 56,5 25,0 65,5 32 23,9 70,3 64,5 26,0 72,0 40 31,0 85,9 83,3 45,0 85,0 50 38,5 99,5 89,4 45,0 89,0	Ocket d d1 D h l1 l2 l3 20 13,5 50,3 48,0 25,0 56,5 68,0 25 18,5 59,0 56,5 25,0 65,5 78,0 32 23,9 70,3 64,5 26,0 72,0 84,5 40 31,0 85,9 83,3 45,0 85,0 100,0 50 38,5 99,5 89,4 45,0 89,0 107,0	Color ocket / 11 d d1 D h l1 l2 l3 L 20 13.5 50.3 48.0 25.0 56.5 68.0 97.0 25 18.5 59.0 56.5 25.0 65.5 78.0 110.0 32 23.9 70.3 64.5 26.0 72.0 84.5 120.5 40 31.0 85.9 83.3 45.0 85.0 100.0 141.0 50 38.5 99.5 89.4 45.0 89.0 107.0 154.0	Colour: Colou	Colour: Colour	Colour: Colour	Colour: Colour: Colou		

- 129,0 139,0 - - 216,0 276,0 152,0 2,441 1 1

Also suitable for vacuum pipes.

1090075051

PP-ball valve, wi	th flange connection	
on both sides	•	

SDR 6 / 7,4 / 9 / 11 / 17,6

Article no.	für Ø	d	l	D	Z	h1	h2	kg	PU	RG
1090090058	90	77,0	210,0	160,0	124,0	150,0	93,0	4,196	1	1
1090110059	110	94,0	260,0	180,0	145,0	165,0	103,0	5,612	1	1
1090160060	160	135,0	310,0	240,0	205,0	210,0	136,5	13,420	1	1

For dimension 125 mm the PP-ball valve Art. no. 1090110059 with flange adapter Art. no. 1050125027 and flange Art. no. 1040110136 is used. For connection with aquatherm green weldable flange adapter (Art. no. 3050090006 - 1054160030) and aquatherm green plastic coated steel flange (Art. no. 1040090135 - 1040160138). Hexagon screw M 16x60 mm for Art. no. 1090090058/1090110059 Hexagon screw M 20x80 mm for Art. no. 1090110059 corresponding flat washer M 16.


NOTICE: These are not included in the above articles.


Electrical drive for ball valve

black / red

for article no. 1090020052 - 1090063057 (*for article no. 1090090058 - 1090110059)

		•	,		
Article no.	Dimension	for Article no.	kg	PU	RG
230 Volt					
9700041489	20	incl. fixtures for 1090020052	1,500	1	1
9700041491	25	incl. fixtures for 1090025053	1,600	1	1
9700041493	32	incl. fixtures for 1090032054	1,600	1	1
9700041495	40	incl. fixtures for 1090040055	1,600	1	1
9700041497	50	incl. fixtures for 1090050056	1,700	1	1
9700041499	63	incl. fixtures for 1090063057	1,700	1	1
9700041603 *	90	incl. fixtures for 1090090058	3,300	1	1
9700041605 *	110	incl. fixtures for 1090110059	3,400	1	1
9700041608 *	160	incl. fixtures for 1090160060	3,700	1	1
24 Volt					
9700041589	20	incl. fixtures for 1090020052	1,500	1	1
9700041591	25	incl. fixtures for 1090025053	1,600	1	1
9700041593	32	incl. fixtures for 1090032054	1,600	1	1
9700041595	40	incl. fixtures for 1090040055	1,600	1	1
9700041597	50	incl. fixtures for 1090050056	1,700	1	1
9700041599	63	incl. fixtures for 1090063057	1,700	1	1
9700041703 *	90	incl. fixtures for 1090090058	3,300	1	1
9700041705 *	110	incl. fixtures for 1090110059	3,400	1	1
9700041708 *	160	incl. fixtures for 1090110059	3,700	1	1









^{*}Flange PN16 200 – 630 mm (Art. no. 9700015934–9700015954) available on request.

^{**}Material: steel/epoxy


Valves__



	or ball valve 1020052- 1090160060	Mate Colo			
Article no.	for Article no.	l	kg	PU	RG
9700098900	1090020052 L:100 mm	100	0,020	1	1
9700098901	1090025053/1090032054 L:100 mm	100	0,025	1	1
9700098902	1090040055/1090050056 L:100 mm	100	0,030	1	1
070000000	10000420E7 -100 mm	100	0 125	1	1



Globe valve for surface installation	— SDR 6 / 7,4 / 9		fusiolen® PP-R /					
Article no.	d	l	D	Z	h	kg	PU	RG
socket welding								
1090020040	20	35,0	29,5	20,5	75,3	0,165	1	1
1090025041	25	38,0	34,0	22,0	75,0	0,172	1	1
1090032042	32	49,0	43,0	31,0	97,0	0,314	1	1
1090040043	40	60,0	52,0	39,5	111,5	0,585	1	1




Concealed v SDR 6 / 7,4 / 9 / 11		Material: Colour:				fusiolen® PP-R / b g					
Article no.	d	l	D	Z	h	h1	h2	kg	PU	RG	
socket welding											
1050020150	20	35,0	29,5	20,5	116,0	28,0	59,0	0,319	1	1	
1050025151	25	38,0	34,0	22,0	116,0	28,0	59,0	0,330	1	1	
1050032152	32	49,0	43,0	31,0	121,0	34,0	59,0	0,416	1	1	


Extension for conce			Material: Colour:	brass chrome	
Article no.	h	kg	PU	RG	
600040900	92,0	0,148	1	1	
600040902	132,0	0,209	1	1	




Concealed vachromium-plated / s	Co	Material: Colour:			fusiolen® PP-R / b green, ch				
Article no.	d	l	D	Z	h	h1	kg	PU	RG
socket welding									
1050020153	20	35,0	29,5	20,5	71,5	28,0	0,258	1	1
1050025154	25	38,0	34,0	22,0	72,0	28,0	0,288	1	1
1050032155	32	/, Q N	/3 N	31 N	82 5	3/. በ	N 374	1	1




$ \begin{array}{c} \textbf{Concealed valve, tamper proof} \\ \textbf{chromium-plated / long design, socket welding} - \text{SDR 6 / 7.4 / 9 / 11} \end{array} $					Co	Material: Colour:			fusiolen® PP-R / brass green, chrom		
Article no.	d	l	D	Z	h	h1	kg	PU	RG		
socket welding											
1050020159	20	35,0	29,5	20,5	109,0	28,0	0,342	1	1		
1050025160	25	38,0	34,0	22,0	109,0	28,0	0,350	1	1		
1050032161	32	49,0	43,0	31,0	115,0	34,0	0,432	1	1		




Concealed v depth 55-10 mm, socket welding	00 mm s	uitable for		on depth 5	5 mm to 10	Mate Colo O			fusiol	len® PP-R / bra green, chro
Article no.	d	l	D	Z	h	h1	h2	kg	PU	RG
socket welding										
1050020156	20	35,0	29,5	20,5	213,0	59,0	147,0	0,357	1	1
1050025157	25	38,0	34,0	22,0	213,0	59,0	147,0	0,369	1	1
1050032158	32	49.0	43.0	31.0	219.0	65.0	153.0	0.455	1	1










110 Article list Article list 111

Valves__






ļ	*****	-	

٤	
<u>, </u>	
	- Z -







1050032185 1050040186

1050050187 1050063188

Stop valve b	ody					Mate Colo	erial: ur:		fusiol	en® PP-	R / brass green
Article no.	d	l	D	D1	Z	h	R	kg	PU	RG	
socket welding											
1090020046	20	35,0	29,5	44,0	20,0	28,0	3/4"	0,082	1	1	
1090025047	25	38,0	34,0	44,0	22,0	28,0	3/4"	0,101	1	1	
1090032048	32	49,0	43,0	52,0	31,0	34,0	1"	0,146	1	1	
10000/00/0		/0.0	F0 0	/n n	00 5	/10	4 4 // !!	0.010	-		

elding — SDR 6 /	/ 7.4 / 9 / 11			Material: Colour:		fusio	len® PP-F
d	l	D	Z	h	kg	PU	RG
20	45,0	34,0	30,5	95,5	0,294	1	1
25	45,0	34,0	29,0	95,5	0,283	1	1
32	56,0	43,0	38,0	111,5	0,421	1	1
40	65,0	52,0	44,5	135,0	0,834	1	1
	20 25 32	d l 20 45,0 25 45,0 32 56,0	20 45,0 34,0 25 45,0 34,0 32 56,0 43,0	d l D z 20 45,0 34,0 30,5 25 45,0 34,0 29,0 32 56,0 43,0 38,0	elding — SDR 6 / 7.4 / 9 / 11 d l D z h 20 45.0 34.0 30.5 95.5 25 45.0 34.0 29.0 95.5 32 56.0 43.0 38.0 111.5	elding — SDR 6 / 7.4 / 9 / 11 d l D z h kg 20 45.0 34.0 30.5 95.5 0.294 25 45.0 34.0 29.0 95.5 0.283 32 56.0 43.0 38.0 111.5 0.421	elding — SDR 6 / 7.4 / 9 / 11 d l D z h kg PU 20 45,0 34,0 30,5 95,5 0,294 1 25 45,0 34,0 29,0 95,5 0,283 1 32 56,0 43,0 38,0 111,5 0,421 1

Non-return va		7,4/9/11			Material: Colour:		fusio	olen® PP-R / b g
Article no.	d	l	D	Z	h	kg	PU	RG
socket welding								
1050020170	20	45,0	34,0	30,5	95,5	0,297	1	1
1050025171	25	45,0	34,0	29,0	95,5	0,292	1	1
1050032172	32	56,0	43,0	38,0	111,5	0,432	1	1
1050040173	An	45 N	52 N	44.5	135 N	0.840	1	1

Draining brain to weld in aquathern SDR 6 / 7,4 / 9 / 11		socket weld	ding			laterial: olour:		fusio	len® PP	-R / bras gree
Article no.	d	l	D	Z	z1	h	kg	PU	RG	
socket welding										
1050020183	20	26,0	34,0	11,5	16,5	71,0	0,098	1	1	
1050025184	25	26.0	34,0	10,0	16,5	71,0	0,096	1	1	

0,140

0,288

Assembly elements


Flow-through back plate elbow 90°


Back plate brass (*stainles			R 6 / 7,4	/ 11					Mate Stand Colou	dards:	fusiolen@			or stainle: DIN EN ISC	
Article no.	d	R	l	l1	D	D1	L	Z	z1	z2	С	kg	PU	RG	
one side socket w	elding														
1040020151	20	1/2"	31,0	31,5	29,5	37,0	51,0	16,5	18,5	13,0	20,0	0,079	10	1	
1040020152	20	3/4"	37,0	37,0	34,0	44,0	54,0	22,5	24,0	13,0	-	0,106	10	1	
1040025153	25	3/4"	37,0	37,0	34,0	44,0	54,0	21,0	24,0	13,0	-	0,105	10	1	
1040025154	25	1/2"	33,5	31,0	34,0	37,0	53,0	17,5	18,0	13,0	20,0	0,080	10	1	
1090020070 *	20	1/2"	31,0	31,5	29,5	37,0	51,0	16,5	18,5	13,0	20,0	0,084	10	1	
1090020071 *	20	3/4"	37,0	37,0	34,0	44,0	54,0	22,5	24,0	13,0	-	0,101	10	1	
1090025072 *	25	3/4"	37,0	37,0	34,0	44,0	54,0	21,0	24,0	13,0	-	0,111	10	1	
1090025073 *	25	1/2"	33,5	31,0	34,0	37,0	53,0	17,5	18,0	13,0	20,0	0,076	10	1	

	90° 20 mm x 1/2"IG x 20 mm		/ O F	F1 0	27.0		20,0	22.5	16.0	-	
double sided soc	ket welding										
Article no.	Dimension	d1	l	12	D	t1	Z	z1	z2	PU	RG


Flow-through b	Material:							fusiolen® PP-R / b						
Article no.	Dimension	d1	ι	12	13	D	L	С	t1	Z	z1	PU	RG	
double sided socket weldin	9													
1050020015 parallel 20) mm x 1/2"IG x 20 mm	7,0	65,0	51,0	45,6	37,0	75,0	28,3	5,5	14,0	42,3	1	1	


Dry constru	iction wal	ll fitting			М	laterial:				brass
Article no.	R	R1	l	l1	L	SW	kg	PU	RG	
9600020114	1/2"	3/4"	10,5	26,0	62,0	30	0,213	10	1	






fusiolen® PP-R / brass








Assembly elements ___



Transition with gasket and	•					7.4 / 11		Materi Standa Colour	ırds:		fusio DIN 16962		R / brass SO 15874 green
Article no.	d	l	l1	12	D	D1	Z	R	SW	kg	PU	RG	
one side socket w	elding												
1050020062	20	37,0	3,5	35,0	29,5	44,0	22,5	1/2"	29	0,154	10	1	
1050025063	25	37,0	3,5	37,0	34,0	44,0	21,0	1/2"	29	0,206	10	1	
E.g. for cistern cor	nection o	r insert wit	h mounti	ng unit (Ar	tNr. 705	0000001 -	7050000	002)					




Transition SDR 6 / 7,4 / 11		v for p	laste	rboar	Material: Colour:						fusiolen® PP-R / b gr		
Article no.	d	l	l1	12	D	D1	Z	R	SW	kg	PU	RG	
one side socket we	lding												
1050020064	20	37,0	18,5	35,0	29,5	44,0	22,5	1/2"	29	0,223	10	1	
with 30 mm thread	countern	ut nasket	and tensio	n washer									



Transition with gasket and t	•			Material: Standards: Colour:			fusiolen® PP-R / DIN 16962, DIN EN ISO					
Article no.	d	l	l1	D	L	Z	R	SW	kg	PU	RG	
one side socket we	lding											
1050020060	20	40,0	13,5	43,5	65,0	25,5	1/2"	29	0,204	10	1	




Back plate ell orass (*stainless steel	Material Standare Colour:		len® PP-R . DIN	2.000	0. 0.0	ess steel SO 15874 green						
Article no.	d	l	11	D	D1	Z	z1	R	kg	PU	RG	
ne side socket welding												
040020156	20	30,0	37,0	29,5	37,0	15,5	24,0	1/2"	0,079	10	1	
1090020074 *	20	30,0	37,0	29,5	37,0	15,5	24,0	1/2"	0,078	10	1	




*stainless steel


Mounting units___

Mounting plate for aquatherm green back plate elbow										Material: Colour:					w	
Article no.	a1	a2	b1	b2	b3	С	d1	d2	f1	f2	h1	h2	kg	PU	RG	
7020000015	28	40	20	30	40	62	80.0	62.0	64	54	18	2 1	0.058	2	43	





	ounting plate galvanised fix back plate elbows as double connection including 2 fixing p					Material: plates and				
4 screws Article no.	d	d1		I1	h	h1	h2	ka	PU	RG
7050000016	40	50,0	25	28	560	50	70	0,546	1	43
			1x							
		1		d ,	× 4=	+ + +				<u> </u>
- +				$\Phi \oplus$) Ø (+	₩ }	100
	+	→ +	+	-	+	→ +	*	-	#	*






Mounting rail ((double and sin	gle)	Materia	l:	Iron / galvanise
Article no.	d1	d2	kg	PU	RG
7050000017	40,0	5,1	0,412	2	43
7050000018	40,0	5,1	0,235	2	43
				115	






Mounting units___




Mounting plate galvanised	Material:	Iron / galvanised

to fix back plate elbows as double connection


Article no.	d	l	l1	12	C	c1	h	h1	kg	PU	RG
7050000020	40	100	50	20	255	40	265	50	0,221	1	43
not suitable for cor	nnection wit	th sound ins	ulation plate	(art. no. 7	7020000015).	We recomm	nend mounti	ng rail art.	no. 7050000	0016	



Assembling jig as water level with 2 plugs 1/2"		Material: Colour:	fusiolen® PP-R green
Article no.	kg	PU	RG
9800050700	0,252	1	3




Plug for pressu	ire tests		Material: Colour:		fusiolen® PP- gree			
Article no.	d	l	L	R	kg	PU	RG	
9800050708	28	55,5	66,0	1/2"	0,022	10	1	
9800050710	34	55 5	44.0	3/4"	N N27	10	1	




Mounting u	ınit, sinç	gle			Material:						
Article no.	b	l	l1	12	h	h1	kg	PU	RG		
7050000002	27,5	118	22,5	55	92,5	122,5	0,278	1	43		

Iron / galvanised



1		Mounting (ınit, doı	uble						Ma
	I I	Article no.	b	l	l1	12	h	h1	13	
		7050000001	27,5	75	25	5	92,5	122,5	239	3
-	100									




Distribution elements__

Mounting unit with one

aquatherm green transition elbowwith one aquatherm green transition elbow, with counternut, gasket and tension washer

Material: fusiolen® PP-R / brass, Iron / galvanised tension washer

7050000004	27,5	22,5	118	55	92,5	122,5	0,434	1	43	
Article no.	b	l	l1	12	h	h1	kg	PU	RG	
tension wasner										




Mounting unit with two


aquatherm green transition elbows
with two aquatherm green transition elbows, with counternut, gasket and tension washer

Article no. b l l1 l2 z h h1 kg PU RG


7050000003 27,5 75 25 5 37,5 92,5 122,5 0,942 1 43




h 4 branci	hes — SD	DR 6 / 7.	4/9/1	1			Colou	ır:				
d1	l	l 1	12	13	D	D1	L	Z	z1	kg	PU	RG
16,0	40	29	57	36	43,0	29,5	245,0	22,0	16	0,148	1	1
20,0	40	29	57	36	43,0	29,5	245,0	22,0	14,5	0,134	1	1
	16,0	16,0 40 20,0 40	16.0 40 29 20.0 40 29	16,0 40 29 57 20,0 40 29 57	16,0 40 29 57 36 20,0 40 29 57 36	16,0 40 29 57 36 43,0 20,0 40 29 57 36 43,0	16,0 40 29 57 36 43,0 29,5 20,0 40 29 57 36 43,0 29,5	16.0 40 29 57 36 43.0 29.5 245.0 20.0 40 29 57 36 43.0 29.5 245.0	16,0 40 29 57 36 43,0 29,5 245,0 22,0	16.0 40 29 57 36 43.0 29.5 245.0 22.0 16 20.0 40 29 57 36 43.0 29.5 245.0 22.0 14.5	16,0 40 29 57 36 43,0 29,5 245,0 22,0 16 0,148 20,0 40 29 57 36 43,0 29,5 245,0 22,0 14,5 0,134	16,0 40 29 57 36 43,0 29,5 245,0 22,0 16 0,148 1 20,0 40 29 57 36 43,0 29,5 245,0 22,0 14,5 0,134 1



Manifold end pi SDR 6 / 7,4 / 9 / 11	ece wi	th fema	le thre	ad	S	laterial: tandards: olour:	DI		len® PP- DIN EN I	
Article no.	d	l	D	L	Z	R	kg	PU	RG	
one side socket welding										
1090032034	32	30,0	43,0	43,0	12,0	1/2"	0,073	1	1	
Transition piece as manifold	endpiece wi	th female thre	ad							




Accessories__



Supporting strap for four-port manifold with clamps, galvanised, double Material: Steel galvanized

Article no.	d	l	l1	l2	h	h1	kg	PU	Re
9600060210	32	210,0	80,0	57,0	66.0	46.0	0,226	2	43



Distribut SDR 6 / 7,4 /		bloc	k p	lum	bing	J				-	Material Colour:	:					fusiole	en® PP- gree	
Artiala na	٦	41		11	12	n	D1	-1	-2		-1	al	ויי	h	l.a	DII	חמ		

Article no.	d	d1	l	11	12	D	D1	Z	z1	z2	С	c1	cl	13	h	kg	PU	RG
socket welding																		
1050025016	25	20,0	60	77,5	79	40,0	29,5	44,0	63	63,0	32	80	100	36	51	0,273	1	1
including 1 nlug	and 2	facton	ore															



Adhesive tape to protect against UV-radiation

Article no.	Dimension	kg	PU	RG
9700010871	Dimension 50 mm x 10 m	0,133	1	1

aquatherm-PP-Primer

for aquatherm PP pipes

Article no.	Container	kg	PU	RG
9700050230	Container: 1l	0,994	1	3
9700050231	Container: 10l	9,269	1	3

aquatherm special top coat

for aquatherm PP pipes

Article no.	Container	kg	PU	RG
9700050232	black Conatiner: 2,5l	3,007	1	3
9700050233	white Container: 2,5l	3,436	1	3

Accessories__

Pipe clamps

suitable for sliding and fixed point installation

Article no.	for pipe diameters	kg	PU	RG
9600060516	16	0,045	50	43
9600060520	20	0,048	50	43
9600060525	25	0,051	50	43
9600060532	32	0,060	50	43
9600060540	40	0,067	50	43
9600060550	50	0,079	50	43
9600060563	63	0,091	25	43
9600060575	75	0,105	25	43
9600060590	90	0,128	25	43
9600060594	110	0,155	25	43
9600060595	125	0,212	25	43
9600060597	160	0,342	25	43
9600060650	200	1,014	1	43
9600060654	250	1,193	1	43
9600060658	315	1,618	1	43

Thread connection: M8 & M10 for 16 - 125 mm | M10 for 160 mm | M16 for 200 - 355 mm

Pipe clamps suitable for fixed point installation

Article no.	for pipe diameters	kg	PU	RI
9600060768	160	8,548	1	4:
9600060770	200	9,449	1	4:
9600060774	250	19,367	1	4:
0400040770	215	22 752	1	

Pipe fastening bow 16-32 mm

Article no.	for pipe diameters	kg	PU	RG
7020016005	for pipes 16-32 mm L=45 mm	0,005	50	43
7020016006	for pipes 16-32 mm L=75 mm	0,007	50	43
7020016007	for pipes 16-32 mm L=45 mm	0,007	50	43
7020016008	for nines 16-32 mm l =75 mm	0.009	50	//3

Plastic pipe clamps 20-40 mm

Article no.	for pipe diameters	kg	PU	RG
7090020011	for pipes 20 mm	0,008	50	43
7090025012	for pipes 25 mm	0,016	30	43
7090032013	for pipes 32 mm	0,017	30	43
7040040014	for nings 40 mm	0.020	30	7.3

Material: Steel








Material: I

Material: Steel













Part of the Solution www.aquatherm.de

